arXiv:1608.07200v2 [cs.DC] 23 Mar 2017

Bulk-synchronous pseudo-streaming algorithms for many-core accelerators

Jan-Willem Buurlage[a,*], Tom Bannink[a,b], Abe Wits[a]

[a] *Centrum Wiskunde & Informatica, Science Park 123, 1098 XG Amsterdam, The Netherlands.*
[b] *QuSoft, Science Park 123, 1098 XG Amsterdam, The Netherlands.*

Abstract

The bulk-synchronous parallel (BSP) model provides a framework for writing parallel programs with predictable performance. An important class of parallel hardware in modern high-performance systems are many-core coprocessors. These often have limited locally memory, and can not be targeted by classic BSP programs. In this paper we extend the BSP model by introducing the notion of bulk-synchronous pseudo-streaming (BSPS) algorithms that are able to run on many-core coprocessors. We generalize the BSP cost function to these algorithms, so that it is possible to predict the running time for programs targeting many-core accelerators and to identify possible bottlenecks. To illustrate how to apply the novel framework, two simple examples of BSPS algorithms are explored. To ensure the portability of BSPS software, we propose a small number of additional primitives as an extension to the BSPlib standard. We introduce a software library called Epiphany BSP that implements the introduced concepts specifically for the Parallella development board. Finally, experimental results are given for BSPS algorithms on the Parallella board.

Keywords: Bulk-synchronous parallel, Streaming algorithm, Software library, Parallel scientific computing, Many-core coprocessor

*Corresponding author
Email address: j.buurlage@cwi.nl (Jan-Willem Buurlage)