

Quantum Algorithms for Graph Connectivity and Formula Evaluation

Stacey Jeffery[1] and Shelby Kimmel[2]

[1]QuSoft and CWI, Amsterdam, the Netherlands
[2]Middlebury College, Middlebury, VT, USA

December 19, 2019

arXiv:1704.00765v3 [quant-ph] 18 Dec 2019

We give a new upper bound on the quantum query complexity of deciding st-connectivity on certain classes of planar graphs, and show the bound is sometimes exponentially better than previous results. We then show Boolean formula evaluation reduces to deciding connectivity on just such a class of graphs. Applying the algorithm for st-connectivity to Boolean formula evaluation problems, we match the $O(\sqrt{N})$ bound on the quantum query complexity of evaluating formulas on N variables, give a quadratic speed-up over the classical query complexity of a certain class of promise Boolean formulas, and show this approach can yield superpolynomial quantum/classical separations. These results indicate that this st-connectivity-based approach may be the "right" way of looking at quantum algorithms for formula evaluation.

1 Introduction

Deciding whether two points are connected in a network is a problem of significant practical importance. In this work, we argue that this problem, st-connectivity, is also important as a quantum algorithmic primitive.

Dürr, Heiligman, Høyer, and Mhalla designed a quantum algorithm for deciding st-connectivity that requires $O(|V|^{3/2})$ queries to the adjacency matrix of a graph on vertex set V [13]. Belovs and Reichardt later discovered an especially elegant span-program-based quantum algorithm for this problem, which is time-efficient and requires only logarithmic space [4]. Belovs and Reichardt's algorithm improves on the query complexity of Dürr et al.'s algorithm when the connecting path is promised to be short (if it exists).

Belovs and Reichardt's st-connectivity algorithm has already been adapted or been used as a subroutine for deciding other graph problems, such as detecting certain subgraphs [4], deciding whether a graph is a forest [8], and deciding whether a graph is bipartite [8].

In this work, we modify the span program algorithm used in [4], inheriting its space and time efficiency, and we restrict to deciding st-connectivity on a class of planar graphs. If the effective resistances of the set of graphs in question (and their planar duals) are small, then we find the quantum algorithm requires far fewer queries than suggested by the analysis in [4]. In fact, we obtain a polynomial to constant improvement in query complexity for some classes of graphs.

Stacey Jeffery: jeffery@cwi.nl, SJ completed parts of this work while at the Institute for Quantum Information and Matter (IQIM), Caltech

Shelby Kimmel: shelby.kimmel@gmail.com, SK completed parts of this work while at the Joint Center for Quantum Information and Computer Science (QuICS), University of Maryland