

Continuous-Variable Protocol for Oblivious Transfer in the Noisy-Storage Model

Fabian Furrer,[1,2] Tobias Gehring,[3] Christian Schaffner,[4,5] Christoph Pacher,[6] Roman Schnabel,[7] and Stephanie Wehner[8]

[1]*NTT Basic Research Laboratories, NTT Corporation, 3-1 Morinosato-Wakamiya, Atsugi, Kanagawa, 243-0198, Japan.*
[2]*Department of Physics, Graduate School of Science, University of Tokyo, 7-3-1 Hongo, Bunkyo-ku, Tokyo, Japan, 113-0033.*
[3]*Department of Physics, Technical University of Denmark, Fysikvej, 2800 Kgs. Lyngby, Denmark*
[4]*Institute for Logic, Language and Computation (ILLC) University of Amsterdam, The Netherlands*
[5]*QuSoft; Centrum Wiskunde & Informatica (CWI); Amsterdam, The Netherlands*
[6]*Center for Digital Safety & Security, AIT Austrian Institute of Technology, 1220 Wien, Austria*
[7]*Institut für Laserphysik und Zentrum für Optische Quantentechnologien, Universität Hamburg, Luruper Chaussee 149, 22761 Hamburg, Germany*
[8]*QuTech, Delft University of Technology, Lorentzweg 1, 2628 CJ Delft, Netherlands*

arXiv:1708.00048v1 [quant-ph] 31 Jul 2017

Cryptographic protocols are the backbone of our information society. This includes two-party protocols which offer protection against distrustful players. Such protocols can be built from a basic primitive called oblivious transfer. We present and experimentally demonstrate here the first quantum protocol for oblivious transfer for optical continuous-variable systems, and prove its security in the noisy-storage model. This model allows to establish security by sending more quantum signals than an attacker can reliably store during the protocol. The security proof is based on new uncertainty relations which we derive for continuous-variable systems, that differ from the ones used in quantum key distribution. We experimentally demonstrate the proposed oblivious transfer protocol for various channel losses by using entangled two-mode squeezed states measured with balanced homodyne detection. Our work enables the implementation of arbitrary two-party quantum cryptographic protocols with continuous-variable communication systems.

Quantum cryptography can be used to perform cryptographic tasks with information theoretical security based on quantum mechanical principles. Most prominent is quantum key distribution (QKD), which allows to implement a communication link that provides theoretical security against eavesdropping [1–3]. Yet, there are other practically important cryptographic protocols such as oblivious transfer (OT), bit commitment, and secure password-based identification. In these so-called two-party protocols, two distrustful parties (Alice and Bob) engage and want to be ensured that the other party cannot cheat or maliciously influence the outcome. Hence, in contrast to QKD, security for these protocols needs not only be established against an outside attacker but even against a distrustful player.

Because of this more demanding security requirement not even quantum physics allows us to implement these tasks securely without additional assumptions [4–10]. An assumption that can be posed on the adversary is to restrict the ability to store information [11, 12]. As scalable and long-lived quantum memories are experimentally still very challenging this assumption can easily be justified. In particular, given any constraint on the size of the adversary's storage device, security for two-party protocols can be obtained by sending more signals during the course of the protocol than the storage device is able to handle. This constraint is known as the bounded and more generally noisy-quantum-storage model [13–15].

Here, we propose and experimentally demonstrate an oblivious transfer protocol based on optical continuous-variable (CV) systems. These systems, like classical optical telecommunication systems, encode information into orthogonal quadratures of the electromagnetic field. We prove the security of the protocol in the noisy-quantum-storage model by establishing new uncertainty relations, different to the one used in quantum key distribution. The experimental demonstration at a telecommunication wavelength is based on an optical CV setup adapted from a recent implementation of CV QKD [16] which uses entangled two-mode squeezed states and subsequent homodyne measurements in two random orthogonal field quadratures.

While we focus here on OT, which is the basic building block from which all other two-party protocols can be derived [17], it is possible to use the same techniques to implement and show security of bit commitment and secure identification. This can be achieved along the same line as proofs for similar protocols for discrete variable (DV) encoding into single photon degrees of freedom (e.g., polarization, path or time) [18, 19]. Using such an encoding OT has been proposed and its security has been studied extensively [13–15, 20–23]. Recently, its experimental demonstration has been reported [19, 24].

In our security proof we derive sufficient conditions for security against a distrustful party having a quantum memory with a bounded classical capacity similar to [20]. The main theoretical ingredients are entropic uncertainty relations for canonically conjugated observables which we derive with and without assumptions on the quantum memory's storage operation and by modelling the quantum memory as bosonic loss channel. While we show that security for arbitrary storage operations is possible, the trade-off in parameters yields very pessimistic rates due to the absence of a tight uncertainty relation. We overcome this problem by assuming that the dishonest party's storage operation is Gaussian.