

2016–
2022



Quantum ciphertext authentication and key recycling with the trap code

Yfke Dulek[1] and Florian Speelman[2]

[1] Centrum voor Wiskunde en Informatica (CWI), QuSoft, and University of Amsterdam
[2] QMATH, Department of Mathematical Sciences, University of Copenhagen

arXiv:1804.02237v1 [quant-ph] 6 Apr 2018

Abstract. We investigate quantum authentication schemes constructed from quantum error-correcting codes. We show that if the code has a property called *purity testing*, then the resulting authentication scheme guarantees the integrity of ciphertexts, not just plaintexts. On top of that, if the code is *strong* purity testing, the authentication scheme also allows the encryption key to be recycled, partially even if the authentication rejects. Such a strong notion of authentication is useful in a setting where multiple ciphertexts can be present simultaneously, such as in interactive or delegated quantum computation. With these settings in mind, we give an explicit code (based on the trap code) that is strong purity testing but, contrary to other known strong-purity-testing codes, allows for natural computation on ciphertexts.

1 Introduction

A central topic in cryptography is authentication: how can we make sure that a message remains unaltered when we send it over an insecure channel? How do we protect a file from being corrupted when it is stored someplace where adversarial parties can potentially access it? And, especially relevant in the current era of cloud computing, how can we let an untrusted third party compute on such authenticated data?

Following extensive research on authentication of classical data, starting with the seminal work by Wegman and Carter [WC81], several schemes have been proposed for authenticating quantum states [BCG+02, ABE08, BGS13]. One notable such scheme is the trap code [BGS13], an encoding scheme that surrounds the data with dummy qubits that function as *traps*, revealing any unauthorized attempts to alter the plaintext data. A client holding the classical encryption key can guide a third party in performing computations directly on the ciphertext by sending input-independent auxiliary quantum states that help bypass the traps, and updating the classical key during the computation. The result is an authenticated output ciphertext.

The trap code distinguishes itself from other quantum authentication schemes in two ways. First, individually-authenticated input qubits can be entangled during the computation, but still be de-authenticated individually. This contrasts for example the Clifford code [ABE08], where de-authentication needs to happen simultaneously on all qubits that were involved in the computation, including any auxiliary ones. Second, the trap code allows for 'authenticated measurements': if a third party measures a ciphertext, the client can verify the authenticity of the result from the classical measurement outcomes only. These two qualities make the trap code uniquely suited for quantum computing on authenticated data. It was originally designed for its use in quantum one-time programs [BGS13], but has found further applications in zero-knowledge proofs for QMA [BJSW16], and in quantum homomorphic encryption with verification [ADSS17].

The extraordinary structure of the trap code is simultaneously its weakness: an adversary can learn information about the secret key by altering the ciphertext in a specific way, and observing