

2018–
2021



Efficient Unitarity Randomized Benchmarking of Few-qubit Clifford Gates

Bas Dirkse,[1,2,*] Jonas Helsen,[1] and Stephanie Wehner[1]

[1] *QuTech, Delft University of Technology, Lorentzweg 1, 2628 CJ Delft, The Netherlands*
[2] *QuSoft, CWI and University of Amsterdam, Science Park 123 1098 XG Amsterdam, The Netherlands*

(Dated: January 17, 2019)

Unitarity randomized benchmarking (URB) is an experimental procedure for estimating the coherence of implemented quantum gates independently of state preparation and measurement errors. These estimates of the coherence are measured by the unitarity. A central problem in this experiment is relating the number of data points to rigorous confidence intervals. In this work we provide a bound on the required number of data points for Clifford URB as a function of confidence and experimental parameters. This bound has favorable scaling in the regime of near-unitary noise and is asymptotically independent of the length of the gate sequences used. We also show that, in contrast to standard randomized benchmarking, a nontrivial number of data points is always required to overcome the randomness introduced by state preparation and measurement errors even in the limit of perfect gates. Our bound is sufficiently sharp to benchmark small-dimensional systems in realistic parameter regimes using a modest number of data points. For example, we show that the unitarity of single-qubit Clifford gates can be rigorously estimated using few hundred data points under the assumption of gate-independent noise. This is a reduction of orders of magnitude compared to previously known bounds.

arXiv:1808.00850v2 [quant-ph] 16 Jan 2019

I. INTRODUCTION

In order to further advance the efforts in building large-scale quantum computers, it is essential to characterize the errors of elementary quantum gates in practical implementations. Randomized benchmarking (RB) [1–4] has in the past years become the standard for assessing the quality of quantum gates [2, 5–10]. This is because RB has a simple and efficiently scalable implementation that characterizes gates errors independently of any state preparation and measurement (SPAM) errors. Since the introduction of randomized benchmarking, several variants have been developed [11–15]. One of these variants is unitarity randomized benchmarking (URB) [12, 16].

This paper is concerned with the URB protocol proposed in [12]. It provides a method to characterize the coherence of errors in implemented quantum gates that is robust against SPAM errors. This characterization of coherence is quantified by the unitarity, a quantity that is independent of the average gate fidelity measured by standard RB. Being able to estimate the unitarity experimentally provides an extra source of information when optimizing experimental implementations of quantum gates [16]. In particular, the unitarity can help to discriminate whether the dominant error process is coherent (i.e., overrotation or calibration errors) or incoherent (i.e., depolarizing or dephasing noise). This information is useful since these two different types of noise are generally reduced in different ways [16, 17]. Additionally, knowing the unitarity of a gate or gate set can be used to get sharper bounds on the credible interval of an interleaved randomized benchmarking experiment [18] and also get improved bounds on the diamond norm error [19–21], which is the relevant metric in the setting of fault-tolerant quantum computing.

The URB protocol is similar to the standard RB protocol and they share many characteristics, like SPAM independent estimation of its figure of merit. It aims only to provide a partial characterization of the gate set (by estimating the unitarity), instead of characterizing the noise completely, which is what channel or gate set tomography for instance aim to do. Since full tomography with rigorous confidence intervals is very resource-intensive [22], in situations where partial noise characterization suffices, more lightweight solutions like RB and URB may be the choice of preference.

In RB-type protocols, the noise-characterizing figure of merit is obtained from the exponential decay rate of the average survival probability with the length of the sequence of gates. For fixed sequence length, the average survival probability is estimated by averaging over a number of randomly sampled gate sequences. An important problem for RB-type procedures is then determining a number of random gate sequences that is practical yet yields a confident estimate of the figure of merit. This problem was realized in the first concrete proposal of RB [4]. Subsequent work focused on resolving this problem in two different, complementary ways. First, statistical tools were applied to allow for confident estimation of the RB decay rate with fewer random gate sequences [23–25]. Second, the underlying distribution from which the RB protocol samples data was analyzed. In particular a sharp bound on the variance of this distribution was derived, which also allows for more resource-efficient estimation of the RB decay rate from measurement data [26, 27]. However, no such analysis exists for the related URB protocol.

Here we analyze the statistics of unitarity randomized benchmarking. The aim of this work is to contribute a solution to the following central question: How many

* b.dirkse@tudelft.nl