

Improved bounds on Fourier entropy and Min-entropy

SRINIVASAN ARUNACHALAM, IBM Research, USA
SOURAV CHAKRABORTY, Indian Statistical Institute, India
MICHAL KOUCKÝ, Computer Science Institute of Charles University, Czech Republic
NITIN SAURABH, Technion - IIT, Israel
RONALD DE WOLF, QuSoft, CWI and University of Amsterdam, the Netherlands

arXiv:1809.09819v2 [cs.CC] 17 Sep 2021

Given a Boolean function $f\colon \{-1,1\}^n \to \{-1,1\}$, define the *Fourier distribution* to be the distribution on subsets of $[n]$, where each $S \subseteq [n]$ is sampled with probability $\widehat{f}(S)^2$. The Fourier Entropy-Influence (FEI) conjecture of Friedgut and Kalai [28] seeks to relate two fundamental measures associated with the Fourier distribution: does there exist a universal constant $C > 0$ such that $\mathbb{H}(\hat{f}^2) \leq C \cdot \mathsf{Inf}(f)$, where $\mathbb{H}(\hat{f}^2)$ is the Shannon entropy of the Fourier distribution of f and $\mathsf{Inf}(f)$ is the total influence of f?

In this paper we present three new contributions towards the FEI conjecture:

(1) Our first contribution shows that $\mathbb{H}(\hat{f}^2) \leq 2 \cdot \mathrm{aUC}^{\oplus}(f)$, where $\mathrm{aUC}^{\oplus}(f)$ is the average unambiguous parity-certificate complexity of f. This improves upon several bounds shown by Chakraborty et al. [20]. We further improve this bound for unambiguous DNFs. We also discuss how our work makes Mansour's conjecture for DNFs a natural next step towards resolution of the FEI conjecture.

(2) We next consider the weaker *Fourier Min-entropy-Influence* (FMEI) conjecture posed by O'Donnell and others [50, 53] which asks if $\mathbb{H}_\infty(\hat{f}^2) \leq C \cdot \mathsf{Inf}(f)$, where $\mathbb{H}_\infty(\hat{f}^2)$ is the min-entropy of the Fourier distribution. We show $\mathbb{H}_\infty(\hat{f}^2) \leq 2 \cdot \mathrm{C}^{\oplus}_{\min}(f)$, where $\mathrm{C}^{\oplus}_{\min}(f)$ is the minimum parity-certificate complexity of f. We also show that for all $\varepsilon \geq 0$, we have $\mathbb{H}_\infty(\hat{f}^2) \leq 2\log(\|\widehat{f}\|_{1,\varepsilon}/(1-\varepsilon))$, where $\|\widehat{f}\|_{1,\varepsilon}$ is the approximate spectral norm of f. As a corollary, we verify the FMEI conjecture for the class of read-k DNFs (for constant k).

(3) Our third contribution is to better understand implications of the FEI conjecture for the structure of polynomials that 1/3-approximate a Boolean function on the Boolean cube. We pose a conjecture: no *flat polynomial* (whose non-zero Fourier coefficients have the same magnitude) of degree d and sparsity $2^{\omega(d)}$ can 1/3-approximate a Boolean function. This conjecture is known to be true assuming FEI and we prove the conjecture unconditionally (i.e., without assuming the FEI conjecture) for a class of polynomials. We discuss an intriguing connection between our conjecture and the constant for the Bohnenblust-Hille inequality, which has been extensively studied in functional analysis.

CCS Concepts: • **Computing methodologies** → **Representation of Boolean functions**; • **Mathematics of computing** → **Information theory**; • **Theory of computation** → *Oracles and decision trees.*

Additional Key Words and Phrases: Fourier analysis of Boolean functions, FEI conjecture, query complexity, polynomial approximation, approximate degree, certificate complexity, DNFs, Mansour's conjecture, entropy

1 INTRODUCTION

Boolean functions $f\colon \{-1,1\}^n \to \{-1,1\}$ naturally arise in many areas of theoretical computer science and mathematics such as learning theory, complexity theory, quantum computing, inapproximability, graph theory, extremal combinatorics, etc. Fourier analysis over the Boolean cube $\{-1,1\}^n$ is a powerful technique that has been used often to analyze problems in these areas. For a survey on the subject, see [50, 69]. One of the most important and longstanding

Authors' addresses: Srinivasan Arunachalam, IBM Research, New York, USA, Srinivasan.Arunachalam@ibm.com; Sourav Chakraborty, Indian Statistical Institute, Kolkata, India, sourav@isical.ac.in; Michal Koucký, Computer Science Institute of Charles University, Prague, Czech Republic, koucky@iuuk.mff.cuni.cz; Nitin Saurabh, Technion - IIT, Haifa, Israel, nitinsau@cs.technion.ac.il; Ronald de Wolf, QuSoft, CWI and University of Amsterdam, Amsterdam, the Netherlands, rdewolf@cwi.nl.