

Two new results about quantum exact learning

Srinivasan Arunachalam[1], Sourav Chakraborty[2], Troy Lee[3], Manaswi Paraashar[2], and Ronald de Wolf[4]

[1]IBM T. J. Watson Research Center

[2]Indian Statistical Institute, Kolkata, India

[3]Centre for Quantum Software and Information, University of Technology Sydney, Australia

[4]QuSoft, CWI and University of Amsterdam, the Netherlands

arXiv:1810.00481v4 [quant-ph] 10 Nov 2021

We present two new results about exact learning by quantum computers. First, we show how to exactly learn a k-Fourier-sparse n-bit Boolean function from $O(k^{1.5}(\log k)^2)$ uniform quantum examples for that function. This improves over the bound of $\widetilde{\Theta}(kn)$ uniformly random *classical* examples (Haviv and Regev, CCC'15). Additionally, we provide a possible direction to improve our $\widetilde{O}(k^{1.5})$ upper bound by proving an improvement of Chang's lemma for k-Fourier-sparse Boolean functions. Second, we show that if a concept class $\mathcal{C}$ can be exactly learned using Q quantum membership queries, then it can also be learned using $O\left(\frac{Q^2}{\log Q}\log|\mathcal{C}|\right)$ *classical* membership queries. This improves the previous-best simulation result (Servedio and Gortler, SICOMP'04) by a $\log Q$-factor.

1 Introduction

1.1 Quantum learning theory

Both quantum computing and machine learning are hot topics at the moment, and their intersection has been receiving growing attention in recent years as well. On the one hand there are particular approaches that use quantum algorithms like Grover search [18] and

Srinivasan Arunachalam: Work done while a Postdoc at Center for Theoretical Physics, MIT and PhD student at QuSoft, CWI, Amsterdam, the Netherlands. Supported by ERC Consolidator Grant 615307 QPROGRESS and MIT-IBM Watson AI Lab under the project *Machine Learning in Hilbert space*. Srinivasan.Arunachalam@ibm.com

Sourav Chakraborty: Work done while on sabbatical at CWI, supported by ERC Consolidator Grant 615307 QPROGRESS. sourav@isical.ac.in

Troy Lee: Partially supported by the Australian Research Council (Grant No: DP200100950). Part of this work was done while at the School for Physical and Mathematical Sciences, Nanyang Technological University and the Centre for Quantum Technologies, Singapore, supported by the Singapore National Research Foundation under NRF RF Award No. NRF-NRFF2013-13. troyjlee@gmail.com

Manaswi Paraashar: manaswi.isi@gmail.com

Ronald de Wolf: Partially supported by ERC Consolidator Grant 615307-QPROGRESS (which ended February 2019), and by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium 024.003.037 and through QuantERA project QuantAlgo 680-91-034. rdewolf@cwi.nl

A conference version of this paper appeared in the proceedings of the 46th International Colloquium on Automata, Languages and Programming (ICALP 19), Leibniz International Proceedings in Informatics (LIPIcs) volume 132, pp.16:1-16:15, 2019.