

Simulating Large Quantum Circuits on a Small Quantum Computer

Tianyi Peng,[1,*] Aram W. Harrow,[2] Maris Ozols,[3] and Xiaodi Wu[4,†]

[1] *Laboratory for Information and Decision Systems, Massachusetts Institute of Technology, Cambridge, MA 02139, USA.*
[2] *Center for Theoretical Physics, Massachusetts Institute of Technology, Cambridge, MA 02139, USA.*
[3] *University of Amsterdam and QuSoft, Amsterdam, the Netherlands.*
[4] *Department of Computer Science, Institute for Advanced Computer Studies, and Joint Center for Quantum Information and Computer Science, University of Maryland, College Park, MD 20742, USA.*

arXiv:1904.00102v2 [quant-ph] 8 Dec 2020

Limited quantum memory is one of the most important constraints for near-term quantum devices. Understanding whether a small quantum computer can simulate a larger quantum system, or execute an algorithm requiring more qubits than available, is both of theoretical and practical importance. In this Letter, we introduce cluster parameters K and d of a quantum circuit. The tensor network of such a circuit can be decomposed into clusters of size at most d with at most K qubits of inter-cluster quantum communication. We propose a *cluster simulation scheme* that can simulate any (K, d)-clustered quantum circuit on a d-qubit machine in time roughly $2^{O(K)}$, with further speedups possible when taking more fine-grained circuit structure into account. We show how our scheme can be used to simulate clustered quantum systems—such as large molecules—that can be partitioned into multiple significantly smaller clusters with weak interactions among them. By using a suitable clustered ansatz, we also experimentally demonstrate that a quantum variational eigensolver can still achieve the desired performance for estimating the energy of the BeH_2 molecule while running on a physical quantum device with half the number of required qubits.

Introduction.—Near-term quantum computing applications will focus on Noisy Intermediate-Scale Quantum (NISQ) devices [1], where quantum memory is limited both in quantity and quality. To meet the memory need of such applications (e.g., quantum simulation [2–4], quantum optimization [5, 6], and quantum machine learning [7, 8]), it is desirable to seek a way to perform computations that require more qubits than physically available, at the cost of additional affordable classical processing.

Trading classical computation for quantum computation is a well-motivated topic of long-standing interest. An extreme example of this is the *(fully) classical simulation* with no quantum computation at all, which is however limited to small dimensions, weak entanglement, or circuits with special gate sets [9–13]. Recently, the possibility of trading classical computation for "virtual qubits" has been discussed in [14]. A systematic understanding of such trade-offs will be crucial for realizing near-term quantum applications.

In this Letter, we introduce a *cluster simulation scheme*, a general framework for simulating large quantum circuits on a quantum computer with a small amount of quantum memory. The performance of our simulation depends on the *cluster parameters* of the given circuits. In particular, we are inspired by the classical *fragmentation* methods and *Quantum Mechanics/Molecular Mechanics* (QM/MM) methods for simulating molecules [15–18] that can be partitioned into multiple weakly interacting clusters of significantly smaller size (e.g., an oligosaccharide consisting of several monosaccharides). Following the spirit of [14] and [15–18], a natural definition of cluster parameters of a quantum circuit should capture the decomposability of the circuit into clusters of bounded size and limited inter-cluster interactions.

Our definition of the cluster parameters is guided by the above intuition, but with an important distinction. Instead of looking into the decomposability of any given circuit, we are concerned about the decomposability of the corresponding *tensor network*, which is inspired by the tensor-network-based classical simulation of quantum circuits [9, 19–21]. One significant advantage of our definition, as we will see below, is to use more flexible decompositions of tensor networks than are possible with simple partitioning of qubits (e.g., as in [14]).

Given our definition of clustered circuits, our main contribution is a scheme to simulate the entire quantum circuit by simulating each cluster on a small quantum machine with classical post-processing. The key difference between our scheme and fully classical simulation schemes [9–13, 22–26] is that we keep part of the computation quantum (i.e., unitary). In particular, we design a method to simulate inter-cluster quantum interactions by classical means. Comparing to "virtual qubits" in [14], our technique can be deemed as trading classical computation for "virtual quantum communication". The cluster simulation scheme applies to general quan-