

Quantum Coupon Collector

Srinivasan Arunachalam* Aleksandrs Belovs† Andrew M. Childs‡
Robin Kothari§ Ansis Rosmanis¶ Ronald de Wolf‖

February 19, 2020

arXiv:2002.07688v1 [quant-ph] 18 Feb 2020

Abstract

We study how efficiently a k-element set $S \subseteq [n]$ can be learned from a uniform superposition $|S\rangle$ of its elements. One can think of $|S\rangle = \sum_{i\in S} |i\rangle/\sqrt{|S|}$ as the quantum version of a uniformly random sample over S, as in the classical analysis of the "coupon collector problem." We show that if k is close to n, then we can learn S using asymptotically fewer quantum samples than random samples. In particular, if there are $n-k = O(1)$ missing elements then $O(k)$ copies of $|S\rangle$ suffice, in contrast to the $\Theta(k \log k)$ random samples needed by a classical coupon collector. On the other hand, if $n-k = \Omega(k)$, then $\Omega(k \log k)$ quantum samples are necessary.

More generally, we give tight bounds on the number of quantum samples needed for every k and n, and we give efficient quantum learning algorithms. We also give tight bounds in the model where we can additionally reflect through $|S\rangle$. Finally, we relate coupon collection to a known example separating proper and improper PAC learning that turns out to show no separation in the quantum case.

1 Introduction

Learning from quantum states is a major topic in quantum machine learning. While this task has been studied extensively [BJ99, SG04, AS05, AS09, AW18, GKZ19, ACL+19], many fundamental questions about the power of quantum learning remain. Determining properties of quantum states has potential applications not only in the context of machine learning, but also as a basic primitive for other types of quantum algorithms and for quantum information processing more generally.

*IBM Research. Part of this work was done while a PhD student at CWI supported by ERC Consolidator Grant 615307-QPROGRESS, and a postdoc at MIT funded by the MIT-IBM Watson AI Lab under the project *Machine learning in Hilbert space*. Srinivasan.Arunachalam@ibm.com

†Faculty of Computing, University of Latvia. Supported by the ERDF project number 1.1.1.2/I/16/113. aleksandrs.belovs@lu.lv

‡Department of Computer Science, Institute for Advanced Computer Studies, and Joint Center for Quantum Information and Computer Science, University of Maryland. Supported by the Army Research Office (grant W911NF-20-1-0015); the Department of Energy, Office of Science, Office of Advanced Scientific Computing Research, Quantum Algorithms Teams and Accelerated Research in Quantum Computing programs; and the National Science Foundation (grant CCF-1813814). amchilds@umd.edu

§Microsoft Quantum and Microsoft Research. robin.kothari@microsoft.com

¶Graduate School of Mathematics, Nagoya University, Japan. Supported by the JSPS International Research Fellowship program and by the JSPS KAKENHI Grant Number JP19F19079. ansis.rosmanis@math.nagoya-u.ac.jp

‖QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by ERC Consolidator Grant 615307-QPROGRESS (which ended Feb 2019), and by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium 024.003.037, and QuantERA project QuantAlgo 680-91-034. rdewolf@cwi.nl