arXiv:2002.08240v2 [quant-ph] 24 Nov 2020

Quantum statistical query learning

Srinivasan Arunachalam* Alex B. Grilo† Henry Yuen‡

Abstract

We propose a learning model called the *quantum statistical learning (*QSQ*)* model, which extends the SQ learning model introduced by Kearns [Kea98] to the quantum setting. Our model can be also seen as a restriction of the quantum PAC learning model: here, the learner does not have direct access to quantum examples, but can only obtain estimates of measurement statistics on them. Theoretically, this model provides a simple yet expressive setting to explore the power of quantum examples in machine learning. From a practical perspective, since simpler operations are required, learning algorithms in the QSQ model are more feasible for implementation on near-term quantum devices.

We prove a number of results about the QSQ learning model. We first show that parity functions, $O(\log n)$-juntas and polynomial-sized DNF formulas are efficiently learnable in the QSQ model, in contrast to the classical setting where these problems are provably hard. This implies that many of the advantages of quantum PAC learning can be realized even in the more restricted quantum SQ learning model.

It is well-known that *weak statistical query dimension*, denoted by $\mathsf{WeakSQDIM}(\mathcal{C})$, characterizes the complexity of learning a concept class $\mathcal{C}$ in the classical SQ model. We show that $\log(\mathsf{WeakSQDIM}(\mathcal{C}))$ is a lower bound on the complexity of QSQ learning, and furthermore it is tight for certain concept classes $\mathcal{C}$. Additionally, we show that this quantity provides strong lower bounds for the small-bias quantum communication model under product distributions.

Finally, we introduce the notion of *private* quantum PAC learning, in which a quantum PAC learner is required to be *differentially private*. We show that learnability in the QSQ model implies learnability in the quantum private PAC model. Additionally, we show that in the private PAC learning setting, the classical and quantum sample complexities are equal, up to constant factors.

1 Introduction

The prospect of using quantum computers to perform machine learning has received much attention lately, given their potential to offer significant speedups for solving certain problems of practical relevance. There has been a flurry of proposed quantum algorithms for performing computations that are ubiquitous in machine learning, ranging from convex optimization, matrix completion, clustering, support vector machines [KP17, BKL+19, LMR13, RML14]. Due to the assumptions required by these quantum algorithms, the evidence for a quantum computational advantage in performing machine learning tasks is murky at best [Tan19, CGL+19]. It is therefore an active area of research to obtain evidence (even conditional) for quantum advantage in machine learning.

*IBM Research. Srinivasan.Arunachalam@ibm.com

†QuSoft and CWI, Amsterdam. alexg@cwi.com

‡University of Toronto. hyuen@cs.toronto.edu