


Hypergraph min-cuts from quantum entropies

Michael Walter[1, 2, a)] and Freek Witteveen[1, b)]
[1)]*Korteweg-de Vries Institute for Mathematics and QuSoft, University of Amsterdam, the Netherlands*
[2)]*Institute for Theoretical Physics, Institute for Language, Logic, and Computation, University of Amsterdam, the Netherlands*

(Dated: September 7, 2021)

The von Neumann entropy of pure quantum states and the min-cut function of weighted hypergraphs are both symmetric submodular functions. In this article, we explain this coincidence by proving that the min-cut function of any weighted hypergraph can be approximated (up to an overall rescaling) by the entropies of quantum states known as stabilizer states. We do so by constructing a novel ensemble of random quantum states, built from tensor networks, whose entanglement structure is determined by a given hypergraph. This implies that the min-cuts of hypergraphs are constrained by quantum entropy inequalities, and it follows that the recently defined hypergraph cones are contained in the quantum stabilizer entropy cones, which confirms a conjecture made in the recent literature.

arXiv:2002.12397v2 [quant-ph] 6 Sep 2021

I. QUANTUM STATES AND HYPERGRAPHS

Given a quantum state ρ on a finite-dimensional tensor product Hilbert space $\mathscr{H} = \bigotimes_{t\in T} \mathscr{H}_t$, where $T := [n] := \{1,\dots,n\}$ is the set of subsystem labels, its *entropy function* $S\colon 2^T \to \mathbb{R}_{\geq 0}$ assigns to each subset $A \subseteq T$ the von Neumann entropy $S(A) = -\operatorname{tr}[\rho_A \log \rho_A]$ of the reduced state $\rho_A = \operatorname{tr}_{T\setminus A}[\rho]$. A basic property of the entropy function is that if ρ is pure, the entropy function is *symmetric*, i.e., $S(A) = S(T\setminus A)$ for all $A \subseteq T$. By a celebrated theorem of Lieb-Ruskai, the entropy function is also *submodular*, meaning that

$$S(A) + S(B) \geq S(A\cup B) + S(A\cap B) \qquad \forall A, B \subseteq T.$$

This inequality is also known as the strong subadditivity of the von Neumann entropy. It is interesting to ask if there are any other entropy inequalities satisfied by arbitrary quantum states. To formalize this, one can define the *quantum entropy cone* $C_n^Q \subseteq \mathbb{R}_{\geq 0}^{2^n}$ as the closure of the set of entropy functions obtained by varying over all pure quantum states on finite-dimensional tensor product Hilbert spaces as above. The result is a closed convex cone.[1] It is a well-known open problem in quantum information theory to determine the cones C_n^Q for $n \geq 5$.[1,2]

One strategy to make progress on this difficult problem has been to restrict to certain classes of quantum states, in order to obtain inequalities that only hold for these specific classes of quantum states. One example is the class of stabilizer states, which are a versatile family of quantum states that have many applications in quantum information theory.[3,4] Thus, let C_n^S denote the closed convex cone generated by the set of entropy functions of pure stabilizer states (over any fixed prime). In general, $C_n^S \subseteq C_n^Q$ is a proper subcone.[5,6] In other words, there are entropy inequalities which are valid for all stabilizer states, but may be violated by general quantum states.

Another class of states of interest are states arising from holographic space-times in the sense of the AdS/CFT correspondence.[7] In that case it is known that (up to small corrections) the entropy function has a geometric interpretation as the size of certain surfaces, as prescribed by the Ryu-Takayanagi formula.[8] This has served as motivation to define the holographic entropy cone, where one considers the cone of entropies as computed by the Ryu-Takayanagi formula on some arbitrary space.[9] This cone has been used to prove various new entropy inequalities for holographic states[9] and is a subject of intense current research in theoretical high energy physics.[10–14]

The holographic entropy cone can be shown to be equal to the cone generated by min-cut functions on graphs.[9] We will now introduce a generalization, by considering *hypergraphs*. Given a hypergraph $G = (V,E)$ and non-negative hyperedge weights $w\colon E \to \mathbb{R}_{\geq 0}$, the *cut function* $c\colon 2^V \to \mathbb{R}_{\geq 0}$ is defined as $c(M) = \sum_{e\in\delta(M)} w(e)$, where $\delta(M)$ is the set of hyperedges that contain vertices both in M and $V\setminus M$. Fixing a subset of terminals $T \subseteq V$, the *min-cut function* $m\colon 2^T \to \mathbb{R}_{\geq 0}$ is then given by $m(A) = \min_{M: M\cap T = A} c(M)$. If all hyperedges have cardinality two then the above reduce to the usual notions for weighted undirected graphs. It is well-known that hypergraph cut functions are symmetric and submodular, just like the quantum entropy function. This property extends directly to min-cut functions, so it holds that

$$\begin{aligned} m(A) &= m(T\setminus A) \qquad \forall A \subseteq T, \\ m(A) + m(B) &\geq m(A\cup B) + m(A\cap B) \qquad \forall A, B \subseteq T. \end{aligned}$$

[a)]Electronic mail: m.walter@uva.nl
[b)]Electronic mail: f.g.witteveen@uva.nl