

2017–
2021

The Measure-and-Reprogram Technique 2.0: Multi-Round Fiat-Shamir and More

Jelle Don[1], Serge Fehr[1,2], and Christian Majenz[1,3]

[1] Centrum Wiskunde & Informatica (CWI), Amsterdam, Netherlands
[2] Mathematical Institute, Leiden University, Netherlands
[3] QuSoft, Amsterdam, Netherlands
jelle.don@cwi.nl, serge.fehr@cwi.nl, c.majenz@uva.nl

arXiv:2003.05207v3 [cs.CR] 7 Mar 2022

Abstract. We revisit recent works by Don, Fehr, Majenz and Schaffner and by Liu and Zhandry on the security of the Fiat-Shamir transformation of Σ-protocols in the quantum random oracle model (QROM). Two natural questions that arise in this context are: (1) whether the results extend to the Fiat-Shamir transformation of *multi-round* interactive proofs, and (2) whether Don et al.'s $O(q^2)$ loss in security is optimal.
Firstly, we answer question (1) in the affirmative. As a byproduct of solving a technical difficulty in proving this result, we slightly improve the result of Don et al., equipping it with a cleaner bound and an even simpler proof. We apply our result to digital signature schemes showing that it can be used to prove strong security for schemes like MQDSS in the QROM. As another application we prove QROM-security of a non-interactive OR proof by Liu, Wei and Wong.
As for question (2), we show via a Grover-search based attack that Don et al.'s quadratic security loss for the Fiat-Shamir transformation of Σ-protocols is optimal up to a small constant factor. This extends to our new multi-round result, proving it tight up to a factor that depends on the number of rounds only, i.e. is constant for any constant-round interactive proof.

1 Introduction

Reprogramming the quantum random oracle. We reconsider the recent work of Don, Fehr, Majenz and Schaffner [DFMS19] on the quantum random oracle model (QROM). On a technical level, they showed how to reprogram the QROM adaptively at *one* input. More precisely, for any oracle quantum algorithm $\mathcal{A}^H$, making q calls to a random oracle H and outputting a pair (x, z) so that some predicate $V(x, H(x), z)$ is satisfied, they showed existence of a "simulator" $\mathcal{S}$ that mimics the random oracle, extracts x from $\mathcal{A}^H$ by measuring one of the oracle queries to H, and then reprograms $H(x)$ to a given value Θ so that z output by $\mathcal{A}^H$ now satisfies $V(x, \Theta, z)$, except with a multiplicative $O(q^2)$ loss in probability (plus a negligible additive loss). We emphasize that the challenging aspect of this problem is that $\mathcal{A}^H$'s queries to H may be in quantum superposition, and thus measuring such a query disturbs the state and thus the behavior of $\mathcal{A}^H$. Still, Don et al. managed to control this disturbance sufficiently. In independent work and using very different techniques, Liu and Zhandry [LZ19] showed a similar kind of result, but with a $O(q^9)$ loss.

As an immediate application of this technique, it is then concluded that the Fiat-Shamir transformation of a Σ-protocol is as secure (in the QROM) as the original Σ-protocol (in the standard model), up to a $O(q^2)$ loss, i.e., any of the typically considered security notions is preserved under the Fiat-Shamir transformation, even in the quantum setting. In combination with prior work on simulating signature queries [Unr17, KLS18], security (in the QROM) of Fiat-Shamir signatures that arise from ordinary Σ-protocols then follows as a corollary.

Given important examples of *multi-round* public-coin interactive proofs, used in, e.g., MQDSS [CHR+16] and for Bulletproofs [BBB+18][1], a natural question that arises is whether these techniques and results extend to the reprogrammability of the QROM at *multiple* inputs and the security of the Fiat-Shamir transformation (in the QROM) of *multi-round* public-coin interactive proofs. Another question is whether the $O(q^2)$ loss (for the original Σ-protocols) is optimal, or whether one might hope for a linear loss as in the classical case.

In this work, we provide answers to both these natural questions — and more.

[1] The security of the original Bulletproofs protocol relies on the hardness of discrete-log; however, work in progress considers post-quantum secure versions [Boo].