

A general framework for randomized benchmarking

J. Helsen,[1] I. Roth,[2,3] E. Onorati,[4] A. H. Werner,[5,6] and J. Eisert[3,7,8]

[1]*QuSoft & Korteweg-de Vries Institute, University of Amsterdam, Science Park 123 1098 XG Amsterdam, The Netherlands*

[2]*Quantum Research Centre, Technology Innovation Institute, Abu Dhabi, UAE*

[3]*Dahlem Center for Complex Quantum Systems, Arnimallee 14, Freie Universität Berlin, 14195 Germany*

[4]*University College London, Dept. of Computer Science 66-72 Gower Street, London WC1E 6EA, United Kingdom*

[5]*Department of Mathematical Sciences, University of Copenhagen, 2100 København, Denmark*

[6]*NBIA, Niels Bohr Institute, University of Copenhagen, Blegdamsvej 17, 2100 København, Denmark*

[7]*Mathematics and Computer Science, Takustraße 9, Freie Universität Berlin, 14195 Berlin, Germany*

[8]*Helmholtz-Zentrum Berlin für Materialien und Energie, Hahn-Meitner-Platz 1, 14109 Berlin, Germany*

Randomized benchmarking refers to a collection of protocols that in the past decade have become central methods for characterizing quantum gates. These protocols aim at efficiently estimating the quality of a set of quantum gates in a way that is resistant to state preparation and measurement errors. Over the years many versions have been developed, however, a comprehensive theoretical treatment of randomized benchmarking has been missing. In this work, we develop a rigorous framework of randomized benchmarking general enough to encompass virtually all known protocols as well as novel, more flexible extensions. Overcoming previous limitations on error models and gate sets, this framework allows us, for the first time, to formulate realistic conditions under which we can rigorously guarantee that the output of any randomized benchmarking experiment is well-described by a linear combination of matrix exponential decays. We complement this with a detailed analysis of the fitting problem associated with randomized benchmarking data. We introduce modern signal processing techniques to randomized benchmarking, prove analytical sample complexity bounds, and numerically evaluate performance and limitations. In order to reduce the resource demands of this fitting problem, we introduce novel, scalable post-processing techniques to isolate exponential decays, significantly improving the practical feasibility of a large set of randomized benchmarking protocols. These post-processing techniques overcome shortcomings in efficiency of several previously proposed methods such as character benchmarking and linear-cross entropy benchmarking. Finally, we discuss, in full generality, how and when randomized benchmarking decay rates can be used to infer quality measures like the average fidelity. On the technical side, our work substantially extends the recently developed Fourier-theoretic perspective on randomized benchmarking by making use of the perturbation theory of invariant subspaces, as well as ideas from signal processing.

arXiv:2010.07974v2 [quant-ph] 5 Apr 2022

I. INTRODUCTION

In the last few years significant steps have been taken towards the development of large-scale quantum computers. A key part of the development of these quantum computers are tools that provide diagnostics, certification, and benchmarking. Particularly for quantum operations, stringent conditions have to be met to achieve fault tolerance. Motivated by this observation, in recent years a significant body of work has been dedicated to the development of tools for the certification and benchmarking of quantum gates. A prominent role in this collection of tools is taken by methods that can be collectively referred to as *randomized benchmarking (RB)*. These methods have risen to prominence because they conform well to the demands of realistic experimental settings. They estimate the magnitude of an average error of a set of quantum gates in a fashion that is robust to errors in *state preparation and measurement* (SPAM) and moreover is, in many settings, efficient, in the sense that the resources required scale polynomially with the number of qubits in the device. The various versions of RB apply sequences of randomly chosen quantum gates of varying length. Small errors are thus amplified with the sequence length, and gate quality measures can be extracted from the dependence of the output data on sequence length.

In RB protocols, group structures feature strongly, in that the gate set considered is in almost all cases a subset of a finite group. Such group structures not only make it possible to efficiently make predictions for error-free sequences and compute inverses, but they also provide the means to analyze the error contribution after averaging. Originally proposed for random unitary gates [1–3], RB is now most prominently executed with gates from the so-called *Clifford group* [4–6], a set of efficiently classically simulatable quantum gates that take a key role specifically in fault tolerant quantum computing [7]. It has also been considered for other (subsets of) finite groups [8–15]. Moreover RB has been generalized to capture other figures of merit of gate sets, such as relative average gate fidelities to specific anticipated target gates [4], fidelities