

2017–
2021

Tight adaptive reprogramming in the QROM

Alex B. Grilo[1], Kathrin Hövelmanns[2], Andreas Hülsing[3], and Christian Majenz[4]

[1] Sorbonne Université, CNRS, LIP6, France
[2] Ruhr-Universität Bochum, Germany
[3] Eindhoven University of Technology, The Netherlands
[4] Centrum Wiskunde & Informatica and QuSoft, Amsterdam, The Netherlands
authors-qrom-reprog@huelsing.net

arXiv:2010.15103v2 [quant-ph] 30 Oct 2020

Abstract. The random oracle model (ROM) enjoys widespread popularity, mostly because it tends to allow for *tight* and *conceptually simple* proofs where provable security in the standard model is elusive or costly. While being the adequate replacement of the ROM in the post-quantum security setting, the quantum-accessible random oracle model (QROM) has thus far failed to provide these advantages in many settings. In this work, we focus on *adaptive reprogrammability*, a feature of the ROM enabling tight and simple proofs in many settings. We show that the straightforward quantum-accessible generalization of adaptive reprogramming is feasible by proving a bound on the adversarial advantage in distinguishing whether a random oracle has been reprogrammed or not. We show that our bound is tight by providing a matching attack. We go on to demonstrate that our technique recovers the mentioned advantages of the ROM in three QROM applications: 1) We give a tighter proof of security of the message compression routine as used by XMSS. 2) We show that the standard ROM proof of chosen-message security for Fiat-Shamir signatures can be lifted to the QROM, straightforwardly, achieving a tighter reduction than previously known. 3) We give the first QROM proof of security against fault injection and nonce attacks for the hedged Fiat-Shamir transform.

Keywords: Post-quantum security, QROM, adaptive reprogramming, digital signature, Fiat-Shamir transform, hedged Fiat-Shamir, XMSS

1 Introduction

Since its introduction, the Random oracle model (ROM) has allowed cryptographers to prove efficient practical cryptosystems secure for which proofs in the standard model have been elusive. In general, the ROM allows for proofs that are conceptually simpler and often tighter than standard model security proofs.

With the advent of post-quantum cryptography, and the introduction of quantum adversaries, the ROM had to be generalized: In this scenario, a quantum adversary interacts with a non-quantum network, meaning that "online" primitives (like signing) stay classical, while the adversary can compute all "offline" primitives (like hash functions) on its own, and hence, in superposition. To account for these stronger capabilities, the quantum-accessible ROM (QROM) was introduced [BDF+11]. While successfully fixing the definitional gap, the QROM does not generally come with the advantages of its classical counterpart:

Part of this work was done while A.G. was affiliated to CWI and QuSoft and part of it was done while A.G. was visiting the Simons Institute for the Theory of Computing. K.H. was supported by the European Union PROMETHEUS project (Horizon 2020 Research and Innovation Program, grant 780701) and the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy (EXC 2092 CASA, 390781972). C.M. was funded by a NWO VENI grant (Project No. VI.Veni.192.159). Date: November 2, 2020