

2022–
2024

Computable lower bounds on the entanglement cost of quantum channels

Ludovico Lami[1,2,3,4,*] and Bartosz Regula[5,†]

[1]*Institut für Theoretische Physik und IQST, Universität Ulm, Albert-Einstein-Allee 11, D-89069 Ulm, Germany*
[2]*QuSoft, Science Park 123, 1098 XG Amsterdam, the Netherlands*
[3]*Korteweg–de Vries Institute for Mathematics, University of Amsterdam, Science Park 105-107, 1098 XG Amsterdam, the Netherlands*
[4]*Institute for Theoretical Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands*
[5]*Department of Physics, Graduate School of Science, The University of Tokyo, Bunkyo-ku, Tokyo 113-0033, Japan*

arXiv:2201.09257v2 [quant-ph] 15 Feb 2023

A class of lower bounds for the entanglement cost of any quantum state was recently introduced in [Nat. Phys. 19, 184 (2023)] in the form of entanglement monotones known as the tempered robustness and tempered negativity. Here we extend their definitions to point-to-point quantum channels, establishing a lower bound for the asymptotic entanglement cost of any channel, whether finite or infinite dimensional. This leads, in particular, to a bound that is computable as a semidefinite program and that can outperform previously known lower bounds, including ones based on quantum relative entropy. In the course of our proof we establish a useful link between the robustness of entanglement of quantum states and quantum channels, which requires several technical developments such as showing the lower semicontinuity of the robustness of entanglement of a channel in the weak*-operator topology on bounded linear maps between spaces of trace class operators.

I. INTRODUCTION

From a modern perspective, one of the fundamental conceptual contributions of classical thermodynamics [1–4] is the realisation that information itself is an entity with observable physical consequences. The advent of quantum mechanics and the epistemological revolution it brought [5–8] have endowed this statement with a more profound meaning. On the other hand, information theory [9] has taught us that information can only be understood by means of the operational tasks it enables. In this sense, it is only natural that a key role in the discipline is played by the processes that allow to manipulate information. In the theory of quantum information [10–12], which aims to combine quantum physics and information theory, such processes are represented by quantum channels [13, 14].

Quantum information is concerned, among other things, with how resources can be interconverted [15, 16]. In this spirit, a great effort has been devoted to the problem of understanding how quantum channels can be transformed into each other. For example, given many uses of a point-to-point quantum channel $\Lambda : A \to B$ connecting Alice's system to Bob's system, one is often interested in determining how much information Alice can transmit to Bob — the quantum capacity of the channel [17–20]. Equivalently, this problem can be thought of as that of understanding how efficiently one can simulate the noiseless qubit identity channel id_2 given Λ.

While this question has received much attention in the last decades, its converse, i.e. the problem of determining the rate at which resources are needed to simulate a given (noisy) quantum channel Λ, although conceptually appealing, is much less studied. Here, the word 'resources' can take, depending on the context, different meanings, with the two main ones referring to entanglement

* ludovico.lami@gmail.com
† bartosz.regula@gmail.com