

2022–
2024

A Post-Quantum Associative Memory

Ludovico Lami

Institut für Theoretische Physik und IQST, Universität Ulm, Albert-Einstein-Allee 11, D-89069 Ulm, Germany
QuSoft, Korteweg-de Vries Institute for Mathematics, and Institute for Theoretical Physics, University of Amsterdam, Science Park, 1098 XG Amsterdam, the Netherlands

Daniel Goldwater

School of Mathematical Sciences, University of Nottingham, University Park, Nottingham NG7 2RD, United Kingdom

Gerardo Adesso

School of Mathematical Sciences, University of Nottingham, University Park, Nottingham NG7 2RD, United Kingdom

E-mail: gerardo.adesso@nottingham.ac.uk

arXiv:2201.12305v3 [quant-ph] 6 Nov 2023

Abstract. Associative memories are devices storing information that can be fully retrieved given partial disclosure of it. We examine a toy model of associative memory and the ultimate limitations it is subjected to within the framework of general probabilistic theories (GPTs), which represent the most general class of physical theories satisfying some basic operational axioms. We ask ourselves how large the dimension of a GPT should be so that it can accommodate 2^m states with the property that any N of them are perfectly distinguishable. Call $d(N, m)$ the minimal such dimension. Invoking an old result by Danzer and Grünbaum, we prove that $d(2, m) = m + 1$, to be compared with $O(2^m)$ when the GPT is required to be either classical or quantum. This yields an example of a task where GPTs outperform both classical and quantum theory exponentially. More generally, we resolve the case of fixed N and asymptotically large m, proving that $d(N, m) \leq m^{1+o_N(1)}$ (as $m \to \infty$) for every $N \geq 2$, which yields again an exponential improvement over classical and quantum theories. Finally, we develop a numerical approach to the general problem of finding the largest N-wise mutually distinguishable set for a given GPT, which can be seen as an instance of the maximum clique problem on N-regular hypergraphs.