

2021–
2022

Optimizing thermalizations

Kamil Korzekwa[1] and Matteo Lostaglio[2,3]

[1] *Faculty of Physics, Astronomy and Applied Computer Science, Jagiellonian University, 30-348 Kraków, Poland*
[2] *Korteweg-de Vries Institute for Mathematics and QuSoft, University of Amsterdam, The Netherlands*
[3] *QuTech, Delft University of Technology, P.O. Box 5046, 2600 GA Delft, The Netherlands*

We present a rigorous approach, based on the concept of continuous thermomajorisation, to algorithmically characterise the full set of energy occupations of a quantum system accessible from a given initial state through weak interactions with a heat bath. The algorithm can be deployed to solve complex optimization problems in out-of-equilibrium setups and it returns explicit elementary control sequences realizing optimal transformations. We illustrate this by finding optimal protocols in the context of cooling, work extraction and catalysis. The same tools also allow one to quantitatively assess the role played by memory effects in the performance of thermodynamic protocols. We obtained exhaustive solutions on a laptop machine for systems with dimension $d \leq 7$, but with heuristic methods one could access much higher d.

arXiv:2202.12616v2 [quant-ph] 5 Aug 2022

Introduction. Thermalization is a ubiquitous process across quantum sciences. A control over interactions between a quantum system and its thermal environment is pivotal for applications ranging from quantum computing to thermodynamics and, quite broadly, for demonstrating and harnessing quantum effects in a variety of experimental platforms. Algorithmic cooling protocols initializing pure ancilla states [1, 2], quantum heat engines [3–5], fridges and heat pumps [6–8], dissipative generation of quantum entanglement [9] – these are but a few examples of tasks involving thermalization stages. These all require the identification of optimal thermalization schedules maximizing corresponding objective functions (ground state population, efficiency, cooling power, entanglement, etc.).

Performing such optimizations in full generality is typically hopeless. In fact, thermalizations are routinely described by quantum Markovian master equations [10], and the problem of characterising all dynamics that can result from the integration of such a class of differential equations is extremely challenging even classically, where it is known as the *embeddability problem* [11, 12]. Despite having been studied for decades in the mathematics literature, general solutions are not known beyond the simplest cases of dimension $d = 2$ and $d = 3$ [13–16].

Here, we start from the observation that the following properties hold in wide generality across standard thermalization models used in atomic, molecular and optical physics, quantum thermodynamics and quantum computing [17–20]:

(P1) The evolution of the system's quantum state is described by a Markovian master equation.

(P2) The thermal state is a fixed point of the evolution.

(P3) Evolutions of the energy occupations ("populations") and that of energetic quantum superpositions ("coherences") decouple.

There are numerous examples of phenomena described by equations satisfying the above assumptions: thermalization strokes in thermal machines [21, 22], weak thermal contact of a quantum system with a large environment [10, 23], an atomic degree of freedom interacting weakly with a thermal radiation field [17], depolarization noise in a quantum computer and strong coupling scenarios via reaction coordinates [24]. For brevity, we will refer to any such dynamical thermalization model as a *Markovian Thermal Process* or an MTP.

The questions we address in this work are:

(Q1) What are the most general constraints characterising the evolution of energy occupations (populations) under an MTP?

(Q2) Given an initial out-of-equilibrium population, can we construct the set of all populations achievable from it under arbitrary MTP?

(Q3) If a transformation from an initial to a final population is possible under MTPs, can we construct an explicit control sequence realizing it?

In what follows we employ the mathematical framework developed in the accompanying paper [25] to provide answers to all these questions. It turns out that (Q1) corresponds to a broad generalization of the well-known entropy production inequalities [26]. Concerning (Q2), we answer the question in the affirmative by providing an explicit verification algorithm and offering its Mathematica implementation [27]. Here, we shall illustrate how this algorithm can be used to solve optimization problems involving cooling, work extraction and catalysis. We also report on a recent work which used our results to show that non-Markovianity boosts the efficiency of thermal bio-molecular switches [28]. Finally, in answering (Q3), we pave the way to the idea of algorithmically generated thermodynamic protocols, as we showcase by using our code to generate the optimal cooling protocol recently introduced in Ref. [29]. These applications build up encouraging evidence that the framework is suitable to perform model-independent optimizations, as well as to algorithmically construct new thermodynamic schemes in