

2019–
2021





2021–
2025

Improved Hardness Results for the Guided Local Hamiltonian Problem

Chris Cade
QuSoft & University of Amsterdam (UvA), Netherlands

Marten Folkertsma
QuSoft & CWI, Netherlands

Sevag Gharibian
Paderborn University, Germany

Ryu Hayakawa
Kyoto University, Japan

François Le Gall
Nagoya University, Japan

Tomoyuki Morimae
Kyoto University, Japan

Jordi Weggemans
QuSoft & CWI, Netherlands

arXiv:2207.10250v3 [quant-ph] 4 Feb 2024

Abstract

Estimating the ground state energy of a local Hamiltonian is a central problem in quantum chemistry. In order to further investigate its complexity and the potential of quantum algorithms for quantum chemistry, Gharibian and Le Gall (STOC 2022) recently introduced the *guided local Hamiltonian problem (GLH)*, which is a variant of the local Hamiltonian problem where an approximation of a ground state (which is called a guiding state) is given as an additional input. Gharibian and Le Gall showed quantum advantage (more precisely, BQP-completeness) for GLH with 6-local Hamiltonians when the guiding state has fidelity (inverse-polynomially) close to 1/2 with a ground state.

In this paper, we optimally improve both the locality and the fidelity parameter: we show that the BQP-completeness persists even with 2-local Hamiltonians, and even when the guiding state has fidelity (inverse-polynomially) close to 1 with a ground state. Moreover, we show that the BQP-completeness also holds for 2-local physically motivated Hamiltonians on a 2D square lattice or a 2D triangular lattice. Beyond the hardness of estimating the ground state energy, we also show BQP-hardness persists when considering estimating energies of *excited* states of these Hamiltonians instead. Those make further steps towards establishing *practical quantum advantage* in quantum chemistry.

2012 ACM Subject Classification Theory of computation → Quantum complexity theory

Keywords and phrases Quantum computing, Quantum advantage, Quantum Chemistry, Guided Local Hamiltonian Problem

Category Track A: Algorithms, Complexity and Games

Related Version This paper is based on our following two technical reports
Previous Version: `https://arxiv.org/abs/2207.10097`
Previous Version: `https://arxiv.org/abs/2207.10250`

Acknowledgements We thank Jonas Helsen for feedback on an earlier draft, and Ronald de Wolf for helpful comments. CC acknowledges support from QuSoft and CWI, as well as the University of Amsterdam (UvA) under a POC (proof of concept) fund. MF and JW were supported by the Dutch Ministry of Economic Affairs and Climate Policy (EZK), as part of the Quantum Delta NL programme. RH, FLG, and TM were supported by MEXT Quantum Leap Flagship Pro-