



(No) Quantum space-time tradeoff for USTCON

Simon Apers[1], Stacey Jeffery*[2], Galina Pass†[3,4], and Michael Walter‡[4]

[1]CNRS, IRIF, Paris
[2]CWI & QuSoft
[3]Korteweg-de Vries Institute for Mathematics & QuSoft, University of Amsterdam
[4]Faculty of Computer Science, Ruhr University Bochum

arXiv:2212.00094v1 [quant-ph] 30 Nov 2022

Abstract

Undirected *st*-connectivity is important both for its applications in network problems, and for its theoretical connections with logspace complexity. Classically, a long line of work led to a time-space tradeoff of $T = \widetilde{O}(n^2/S)$ for any S such that $S = \Omega(\log(n))$ and $S = O(n^2/m)$. Surprisingly, we show that quantumly there is no nontrivial time-space tradeoff: there is a quantum algorithm that achieves both optimal time $\widetilde{O}(n)$ and space $O(\log(n))$ simultaneously. This improves on previous results, which required either $O(\log(n))$ space and $\widetilde{O}(n^{1.5})$ time, or $\widetilde{O}(n)$ space and time. To complement this, we show that there is a nontrivial time-space tradeoff when given a lower bound on the spectral gap of a corresponding random walk.

1 Introduction

For an undirected graph $G = (X, E)$ on $n = |X|$ vertices and $m = |E|$ edges, with $s, t \in X$, *st*-connectivity or USTCON is the problem of deciding whether s and t are in the same component. This problem has applications in many other graph and network problems, and is of theoretical importance for its connection with space complexity (see e.g. [Wig92]). In particular, USTCON is complete for the class *symmetric logspace*, SL, which was shown to be equal to *logspace*, L, by exhibiting a classical deterministic logspace algorithm for USTCON [Rei08]. In this paper, we consider quantum algorithms for this problem.

There are different versions of the problem USTCON depending on how G is accessed. If G is given as an adjacency matrix, we denote the problem $\text{USTCON}_{\text{mat}}$. If G is given as an array of arrays, one for each vertex, enumerating the neighbours, we denote the problem $\text{USTCON}_{\text{arr}}$. [1] If one only cares about space complexity, these problems are equivalent, but the same is not true of time complexity: adjacency queries can simulate an array query, and vice versa, in logspace, but there is a non-negligible time overhead.

A classical deterministic algorithm based on breadth-first search or depth-first search can solve $\text{USTCON}_{\text{arr}}$ in $\widetilde{O}(m)$ time, using $\widetilde{O}(n)$ space. Using a random walk, the space complexity

*Supported by ERC STG grant 101040624-ASC-Q, NWO Klein project number OCENW.Klein.061, and ARO contract no W911NF2010327. SJ is a CIFAR Fellow in the Quantum Information Science Program.

†Supported by the National Agenda for Quantum Technologies (NAQT), as part of the Quantum Delta NL programme.

‡Supported by the European Research Council (ERC) through ERC Starting Grant 101040907-SYMOPTIC, the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy - EXC 2092 CASA - 390781972, the Federal Ministry of Education and Research (BMBF) through project Quantum Methods and Benchmarks for Resource Allocation (QuBRA), and NWO grant OCENW.KLEIN.267.

[1]There are variations on the details of this model. For now, we allow $\text{USTCON}_{\text{arr}}$ to stand in for multiple variations of the array access model, but precise details of the variations can be found in Section 3.