
2020–
2024


2021–
2025




2020–
2024



arXiv:2308.04166v1 [quant-ph] 8 Aug 2023

Security of a Continuous-Variable based Quantum Position Verification Protocol

Rene Allerstorfer[1], Llorenç Escolà-Farràs[1,2], Arpan Akash Ray[3], Boris Škorić[3], Florian Speelman[1,2], and Philip Verduyn Lunel[1]

[1] *QuSoft, CWI Amsterdam, The Netherlands*
[2] *Multiscale Networked Systems, Informatics Institute, University of Amsterdam, The Netherlands*
[3] *TU Eindhoven, The Netherlands*

August 9, 2023

Abstract

In this work we study quantum position verification with continuous-variable quantum states. In contrast to existing discrete protocols, we present and analyze a protocol that utilizes coherent states and its properties. Compared to discrete-variable photonic states, coherent states offer practical advantages since they can be efficiently prepared and manipulated with current technology. We prove security of the protocol against any unentangled attackers via entropic uncertainty relations, showing that the adversary has more uncertainty than the honest prover about the correct response as long as the noise in the quantum channel is below a certain threshold. Additionally, we show that attackers who pre-share one continuous-variable EPR pair can break the protocol.

1 Introduction

Position-based cryptography allows for protocols in which the geographical location of a party is used as a cryptographic credential. Consider, for example, the establishment of trust between you and someone at a claimed location. Or sending a confidential message that can only be decrypted at a specific location. Part of position-based cryptography is the task of position verification, where an untrusted prover aims to convince verifiers that he is present at a certain position P.

This primitive was first introduced by Chandran, Goyal, Moriarty, and Ostrovsky [CGMO09], and it has been shown that no classical position verification protocol can exist, due to a universal attack based on cloning input information. This attack fails in the quantum setting because of the no-cloning theorem [WZ82]. Quantum position verification (QPV) has been studied[1] since the early 2000s by several authors [KMSB06, Mal10a, Mal10b, LL11], but despite the failure of the classical universal attack, a universal quantum attack has since been found [BCF+14, BK11]. However, this attack consumes an amount of entanglement exponential in the input size and is therefore not practically feasible. Thus, we may still find secure QPV protocols in the bounded-entanglement model.

The analysis of the entanglement resources needed turns out to be a deep question in its own right [BFSS13, Spe16, DC22, CM22, BCS22, ABM+23]. Many protocols have since been proposed [CL15, ABSV21, GC19, LLQ22] and different security models have been studied [Unr14, GLW16, Dol19, ABSV22]. Recent work has focused on the practicality of implementing position-verification protocols. Aspects such as channel loss and error tolerance of certain QPV protocols must be taken into account [ABSV22, EFS22].

Almost all previously studied QPV protocols have in common that they contain only finite-dimensional quantum systems. The study of QPV using continuous-variable (CV) quantum information, i.e., using infinite-dimensional quantum states, was first mentioned in [QS15], in which a

[1] under the name of 'quantum tagging'