

Streaming quantum state purification

Andrew M. Childs[1,2], Honghao Fu[1,2,3,6], Debbie Leung[1,4], Zhi Li[4], Maris Ozols[5], and Vedang Vyas[1]

[1]Institute for Quantum Computing, University of Waterloo, Waterloo, ON, N2L 3G1, Canada
[2]Department of Computer Science, Institute for Advanced Computer Studies, and Joint Center for Quantum Information and Computer Science, University of Maryland, College Park, MD 20742, USA
[3]Massachusetts Institute of Technology, 77 Massachusetts Ave., Cambridge, MA 02139, USA
[4]Perimeter Institute for Theoretical Physics, 31 Caroline St. N., Waterloo, ON N2L 2Y5, Canada
[5]QuSoft and University of Amsterdam, Science Park 123, 1098 XG, Amsterdam, the Netherlands
[6]Concordia Institute of Information Systems Engineering, Concordia University, 1455 Blvd. De Maisonneuve Ouest, Montreal, QC H3G 1M8, Canada

arXiv:2309.16387v4 [quant-ph] 1 Jan 2025

Quantum state purification is the task of recovering a nearly pure copy of an unknown pure quantum state using multiple noisy copies of the state. This basic task has applications to quantum communication over noisy channels and quantum computation with imperfect devices, but has primarily been studied previously for the case of qubits. We derive an efficient purification procedure based on the swap test for qudits of any dimension, starting with any initial error parameter. Treating the initial error parameter and the dimension as constants, we show that our procedure has sample complexity asymptotically optimal in the final error parameter. Our protocol has a simple recursive structure that can be applied when the states are provided one at a time in a streaming fashion, requiring only a small quantum memory to implement.

Contents

1 Introduction **2**

2 Purification using the swap test **4**
2.1 The swap test . . . 4
2.2 The swap test gadget . . . 5
2.3 Recursive purification based on the swap test . . . 7
2.4 Non-recursive stack-based implementation . . . 8

3 Analysis of recursive purification **9**
3.1 Monotonicity relations . . . 9
3.2 Asymptotics of the error parameter . . . 10
3.3 Expected sample complexity . . . 21

4 Applications **24**
4.1 Simon's problem with a faulty oracle . . . 24
4.2 Relationship to mixedness testing and quantum state tomography . . . 26
4.3 Relationship to quantum majority vote problem . . . 27

5 Sample complexity lower bound **27**

6 Conclusions **29**

A Output error parameter from swap test as a function of input errors **33**