




# Global Variational Quantum Circuits for Arbitrary Symmetric State Preparation


Liam J. Bond,[1,2,3,*] Matthew J. Davis,[3] Jiří Minář,[1,2,4] Rene Gerritsma,[1,2] Gavin K. Brennen,[5] and Arghavan Safavi-Naini[1,2,3]

[1] *Institute of Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, the Netherlands*
[2] *QuSoft, Science Park 123, 1098 XG Amsterdam, the Netherlands*
[3] *ARC Centre of Excellence for Engineered Quantum Systems, School of Mathematics and Physics, University of Queensland, St Lucia, QLD 4072, Australia*
[4] *CWI, Science Park 904, 1098 XH Amsterdam, the Netherlands*
[5] *ARC Centre of Excellence for Engineered Quantum Systems, School of Mathematical and Physical Sciences, Macquarie University, Sydney, NSW 2109, Australia*



(Dated: June 24, 2025)



Quantum states that are symmetric under particle exchange play a crucial role in fields such as quantum metrology and quantum error correction. We use a variational circuit composed of global one-axis twisting and global rotations to efficiently prepare arbitrary symmetric states, i.e. any superposition of Dicke states. The circuit does not require local addressability or ancilla qubits and thus can be readily implemented in a variety of experimental platforms including trapped-ion quantum simulators and cavity QED systems. We provide analytic and numerical evidence that any $N$-qubit symmetric state can be prepared in $2N/3$ steps. We demonstrate the utility of our protocol by preparing (i) metrologically useful $N$-qubit Dicke states of up to $N = 300$ qubits in $\mathcal{O}(1)$ gate steps with theoretical infidelities $1-\mathcal{F} < 10^{-3}$, (ii) the $N = 9$ Ruskai codewords in $P = 4$ gate steps with $1-\mathcal{F} < 10^{-4}$, and (iii) the $N = 13$ Gross codewords in $P = 7$ gate steps with $1-\mathcal{F} < 10^{-4}$. Focusing on trapped-ion platforms, for the $N = 9$ Ruskai and $N = 13$ Gross codewords we estimate that the protocol achieves fidelities $\gtrsim 95\%$ in the presence of typical experimental noise levels, thus providing a pathway to the preparation of a wide range of useful highly-entangled quantum states.



arXiv:2312.05060v2 [quant-ph] 21 Jun 2025


The operation of a quantum computer relies on our ability to prepare highly entangled quantum states, both as a step for quantum algorithms, and as codewords for quantum error correction (QEC). Despite recent remarkable experimental progress towards fault-tolerant quantum computing [1–3], the fragility of multi-partite entanglement to noise limits the fidelity of state preparation. Furthermore, the lack of single-site addressing in some experimental platforms has typically limited the variety of states that can be prepared to e.g. squeezed states. In light of these limitations, the choice of QEC scheme is important. Depending on its properties, certain QEC schemes may offer advantages both in terms of the types of errors that they can protect against [4], as well as their suitability of implementation to the particular hardware. One promising approach utilizes codewords which are symmetric states, i.e. superpositions of Dicke states [5–7]. The Dicke states are also relevant for quantum metrology [8], including error-corrected quantum sensing [9], quantum storage [10, 11] and quantum networking [12]. The need to overcome the intrinsic noise in NISQ devices has motivated the design of symmetric state preparation protocols that minimize the circuit depth. In particular, symmetric states have been prepared using one- and two-qubit gate circuits with depth $\mathcal{O}(N)$ [13, 14], and specific Dicke states with constant depth using measurements and classical computation [15].

In this article, we demonstrate that *arbitrary* superpositions of Dicke states can be engineered using linear depth circuits with only global control. Specifically, we utilize a variational quantum circuit consisting of only global one-axis twisting and global rotations, and thus do not demand local addressability nor ancilla qubits. We provide analytic and numerical evidence that the number of steps to synthesize an arbitrary $N$-qubit symmetric states scales as $2N/3$. Focusing on applications to QEC codewords, we show that only $P = 4$ and $P = 7$ steps are required to prepare QEC codewords of the $N = 9$ Ruskai [6] and $N = 13$ Gross [7] codes with infidelity $1-\mathcal{F} < 10^{-4}$, respectively. We discuss the possible implementation in trapped ions, including a detailed analysis of expected sources of error. The limited resources required by our protocol make it immediately realizable on a broad range of experimental quantum simulation platforms.

*Dicke states:* We consider an ensemble of $N$ qubits. The collective spin operators are defined as $J_\alpha = (1/2)\sum_{j=1}^{N}\sigma_j^\alpha$ where $\alpha \in \{x, y, z\}$ and $\sigma_j^\alpha$ is the Pauli operator acting on the $j$-th qubit. Dicke states, denoted $|J, M\rangle$, are simultaneous eigenstates of the total spin operator $J^2 = J_x^2 + J_y^2 + J_z^2$ and $J_z$. The quantum numbers $J$ and $M$ are defined by $J^2|J, M\rangle = J(J+1)|J, M\rangle$, $J_z|J, M\rangle = M|J, M\rangle$ with $J \in \{0, \ldots, N/2\}$, and $M \in \{-J, \ldots, J\}$. We focus on the $N+1$ symmetric $J \equiv N/2$ Dicke states, which in the single-particle $\sigma_z$ basis are

$$|J = N/2, M\rangle = \frac{1}{\sqrt{\lambda}}\sum_{\mathcal{P}}(|1\rangle^{J+M} \otimes |0\rangle^{J-M}), \quad (1)$$

where the normalisation factor is $\lambda = \binom{2J}{J+M}$, and where the summation is over all permutations $\mathcal{P}$ of the


* L.J.Bond@uva.nl