



Multidimensional Quantum Walks, Recursion, and Quantum Divide & Conquer

Stacey Jeffery[1,2] and Galina Pass[2]

[1]CWI, Amsterdam
[2]QuSoft & University of Amsterdam

May 9, 2024

arXiv:2401.08355v2 [quant-ph] 7 May 2024

Abstract

We introduce an object called a *subspace graph* that formalizes the technique of multidimensional quantum walks. Composing subspace graphs allows one to seamlessly combine quantum and classical reasoning, keeping a classical structure in mind, while abstracting quantum parts into subgraphs with simple boundaries as needed. As an example, we show how to combine a *switching network* with arbitrary quantum subroutines, to compute a composed function. As another application, we give a time-efficient implementation of quantum Divide & Conquer when the sub-problems are combined via a Boolean formula. We use this to quadratically speed up Savitch's algorithm for directed *st*-connectivity.

1 Introduction

There are a number of graphical ways of reasoning about how the steps or subroutines of a classical algorithm fit together. For example, it is natural to think of a (randomized) classical algorithm as a (randomized) decision tree (or branching program), where different paths are chosen depending on the input, as well as random choices made by the algorithm. A deterministic algorithm gives rise to a computation *path*, a randomized algorithm to a computation *tree*. The edges of a path or tree, representing steps of computation, might be implemented by some subroutine that is also realized by a path (or tree) – we can abstract the subroutine's details by viewing it as an edge, or zoom in and see those details, as convenient. More generally, we often think of a classical randomized algorithm as a random walk on a (possibly directed) graph, where there may be multiple parallel paths from point a to point b, with the cost of getting from a to b being derived from the expected length of these paths.

This picture appears to break down for quantum algorithms, at least in the standard circuit model. A quantum circuit can be thought of as a path, with edges representing its steps, but it is not immediately clear how to augment this reasoning with subroutines. Consider calling subroutines with varying time complexities $\{T_i\}_i$ in superposition. Even if the subroutines are all classical deterministic, in the standard quantum circuit model, we tend to incur a cost of $\max_i T_i$ if we call a superposition of subroutines, since we must wait for the slowest subroutine to finish before we can apply the next step of the computation. This problem was addressed in [Jef22], where the technique of multidimensional quantum walks [JZ23] was used to show how to get an average in place of a max in several settings where a quantum algorithm calls subroutines in superposition: a general setting, as well as the setting of quantum walks. The intuition behind this work is that a quantum walk does keep the classical intuition of parallel paths representing a superposition of possible computations, and *any* quantum algorithm can be viewed as some sort of a quantum walk on a simple underlying graph (something like a path), but with some additional structure associated with it.

Multidimensional quantum walks, which we study more formally in this paper as an object than has been done previously, are valuable as a way of combining quantum and classical reasoning. A quantum algorithm can be abstracted as a graph with perhaps complicated internal structure, but a