

2021–
2025



Port-Based State Preparation and Applications

Garazi Muguruza and Florian Speelman

QuSoft & Informatics Institute, University of Amsterdam, Netherlands

arXiv:2402.18356v2 [quant-ph] 4 Dec 2024

We introduce Port-Based State Preparation (PBSP), a teleportation task where Alice holds a complete classical description of the target state and Bob's correction operations are restricted to only tracing out registers. We show a protocol that implements PBSP with error decreasing exponentially in the number of ports, in contrast to the polynomial trade-off for the related task of Port-Based Teleportation, and we prove that this is optimal when a maximally entangled resource state is used.

As an application, we introduce approximate Universal Programmable Hybrid Processors (UPHP). Here the goal is to encode a unitary as a quantum state, and the UPHP can apply this unitary to a quantum state when knowing its classical description. We give a construction that needs strictly less memory in terms of dimension than the optimal approximate Universal Programmable Quantum Processor achieving the same error. Additionally, we provide lower bounds for the optimal trade-off between memory and error of UPHPs.

1 Introduction

Quantum teleportation [Ben+93] is a fundamental task in quantum information processing: Two parties, Alice and Bob, can implement a quantum channel by means of a classical channel and one entangled quantum bit shared between the two parties. Although an infinitely-precise description of a quantum state would require an infinite number of classical bits to describe, quantum teleportation allows an observer who cannot access the infinite information in a quantum state to send this information only with 2-bits of classical communication and an entangled qubit.

Standard teleportation is a protocol where the transmitted quantum state is unknown, but what if Alice knows which quantum state she would like to transmit? Of course, she could first create the state and then use a standard teleportation protocol, but it might open up the option for other protocols. This variant of teleportation is called remote state preparation (RSP) [Ben+01], and can indeed be performed more efficiently; for instance, asymptotically only one bit of classical communication is necessary to transmit a qubit.

Port-based teleportation [IH08] (PBT) is a variant of teleportation where the receiver's correction operation is very simple; after receiving classical information from Alice, Bob simply picks one of the subsystems, or *ports*, and traces out the rest of his part of the entangled resource state. This form of the correction operation allows Bob to perform quantum operations on the output of the protocol before receiving the correct port – this property makes PBT a useful primitive for various tasks in quantum information, including proving bounds on channel discrimination [Pir+19], universal programmable quantum

Garazi Muguruza: g.muguruzalasa@uva.nl
Florian Speelman: f.speelman@uva.nl