

2021–
2026

arXiv:2404.06282v1 [quant-ph] 9 Apr 2024

Simple algorithms to test and learn local Hamiltonians

Francisco Escudero Gutiérrez*

April 10, 2024

Abstract

We consider the problems of testing and learning an n-qubit k-local Hamiltonian from queries to its evolution operator with respect the 2-norm of the Pauli spectrum, or equivalently, the normalized Frobenius norm. For testing whether a Hamiltonian is ε_1-close to k-local or ε_2-far from k-local, we show that $O(1/(\varepsilon_2 - \varepsilon_1)^8)$ queries suffice. This solves two questions posed in a recent work by Bluhm, Caro and Oufkir. For learning up to error ε, we show that $\exp(O(k^2 + k\log(1/\varepsilon)))$ queries suffice. Our proofs are simple, concise and based on Pauli-analytic techniques.

1 Introduction

In this work we consider the problems of testing and learning a local Hamiltonian from its time evolution operator. These kinds of Hamiltonians govern the dynamics of many physical systems, which motivates the problem of testing if an unknown Hamiltonian is local and, if it is local, to learn it in an efficient way. In fact, there is vast and recent literature about learning a local Hamiltonian from its time evolution operator [dSLCP11, BAL19, ZYLB21, HKT22, WKR+22, YSHY23, Car23, DOS23, HTFS23, CW23, LTN+23, MBC+23, SFMD+24, GCC24], but the first testing algorithm was only proposed recently by Bluhm, Caro and Oufkir [BCO24a]. There are also many of results about learning a Hamiltonian from its Gibbs state [AAKS21, HKT22, RSF23, ORSFW23, BLMT23, GCC24], but in this work we will only consider the model where one accesses the Hamiltonian through queries to its evolution operator.

An n-qubit Hamiltonian H is a self-adjoint operator acting on $(\mathbb{C}^2)^{\otimes n}$. As such, it can be expanded in terms of the Pauli strings as

$$H = \sum_{x\in\{0,1,2,3\}^n} h_x \sigma_x,$$

where h_x are real numbers and $\sigma_x = \otimes_{i\in[n]}\sigma_{x_i}$, where $\sigma_0 = \mathrm{Id}_2$, $\sigma_1 = X$, $\sigma_2 = Y$, $\sigma_3 = Z$. The coefficients h_x are known as the Pauli spectrum of the Hamiltonian. A Hamiltonian H is k-local if it is supported on Pauli strings that act trivially on all but at most k qubits. In other words, H is k-local if $h_x = 0$ for all $x \in \{0,1,2,3\}^n$ that take values different from 0 on more than k sites. If H is the Hamiltonian describing the dynamics of a certain physical system, then the states of that system evolve according to the time evolution operator $U(t) = e^{-iHt}$. This means that if $\rho(0)$ is the state at time 0, at time t the state will have evolved to $\rho(t) = U(t)\rho(0)U^\dagger(t)$. Hence,

*Qusoft and CWI feg@cwi.nl