

2021–
2026

Learning low-degree quantum objects

Srinivasan Arunachalam* Arkopal Dutt † Francisco Escudero Gutiérrez‡ Carlos Palazuelos §

May 20, 2024

arXiv:2405.10933v1 [quant-ph] 17 May 2024

Abstract

We consider the problem of learning low-degree quantum objects up to ε-error in ℓ_2-distance. We show the following results: (i) unknown n-qubit degree-d (in the Pauli basis) quantum channels and unitaries can be learned using $O(1/\varepsilon^d)$ queries (independent of n), (ii) polynomials $p : \{-1,1\}^n \to [-1,1]$ arising from d-query quantum algorithms can be classically learned from $O((1/\varepsilon)^d \cdot \log n)$ many random examples $(x, p(x))$ (which implies learnability even for $d = O(\log n)$), and (iii) degree-d polynomials $p : \{-1,1\}^n \to [-1,1]$ can be learned through $O(1/\varepsilon^d)$ queries to a quantum unitary U_p that block-encodes p. Our main technical contributions are new Bohnenblust-Hille inequalities for quantum channels and completely bounded polynomials.

1 Introduction

Computational learning theory refers to the mathematical framework for understanding machine learning models and quantifying their complexity. The seminal result of Leslie Valiant [Val84] (who introduced the Probably Approximately Correct (PAC) model) gives a complexity-theoretic definition of what it means for a class of functions $f : \{0,1\}^n \to \{0,1\}$ to be learnable information-theoretically and computationally.

One of the foundational results in computational learning theory is the one of Linial, Mansour and Nisan [LMN93] who showed that AC_0, or constant-depth n-bit classical circuits consisting of AND, OR and NOT gates, can be learned in quasi-polynomial time. A crucial aspect of their proof is the following structural theorem: if a Boolean function f is computable by AC_0, then f can be approximated by a *low-degree polynomial*. Using this structural property, the learning algorithm approximates the coefficients of all the low-degree monomials of f in the PAC model and hence approximately learns the unknown AC_0 function. Since their work, the notion of Boolean functions being low-degree themselves or being approximated by low-degree polynomials has been a central technique [BT21] to obtain new learning algorithms. Furthermore, low-degree approximations have played a significant role in theoretical computer science topics such as quantum computing, circuit complexity, learning theory and cryptography.

In the last few years, there have been several works in quantum learning theory where the goal has been to learn an unknown object on a quantum computer given various access models to

*IBM Quantum. Srinivasan.Arunachalam@ibm.com
†IBM Quantum arkopal@ibm.com
‡Qusoft and CWI feg@cwi.nl
§UCM and ICMAT carlospalazuelos@mat.ucm.es