

2021–
2025



arXiv:2405.13717v2 [quant-ph] 9 Apr 2025

Lossy-and-Constrained Extended Non-Local Games with Applications to Quantum Cryptography

Llorenç Escolà-Farràs[1,2] and Florian Speelman[1,2]

[1]QuSoft, CWI Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands
[2]Multiscale Networked Systems (MNS), Informatics Institute, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands

Extended non-local games are a generalization of monogamy-of-entanglement games, played by two quantum parties and a quantum referee that performs a measurement on their local quantum system. Along the lines of the NPA hierarchy, the optimal winning probability of those games can be upper bounded by a hierarchy of semidefinite programs (SDPs) converging to the optimal value. Here, we show that if one extends such games by considering *constraints* and *loss*, motivated by experimental errors and loss through quantum communication, the convergence of the SDPs to the optimal value still holds. We give applications of this result, and we compute SDPs that show tighter security of protocols for relativistic bit commitment, quantum key distribution, and quantum position verification.

Contents

1 Introduction **2**

2 Preliminaries **3**

3 Lossy-and-constrained extended non-local games **3**
3.1 Convergence of $\omega_{comm}(\mathcal{G}_{C,\eta})$ via SDPs 7

4 Concrete games **12**
4.1 Constrained BB84 monogamy-of-entanglement game 12
4.2 Alice guessing game with constraints 13
4.3 Local guessing game 14
4.4 Lossy monogamy-of-entanglement games 16

5 Applications to quantum cryptography **19**
5.1 Application to relativistic Bit Commitment (with loss) 19
5.1.1 Security for dishonest Charlie 22
5.2 Application to device-independent quantum key distribution 23
5.3 Application to quantum position verification 24
5.3.1 Security for 2-fold parallel repetition of $\mathrm{QPV}^{\eta}_{\mathrm{BB84}}$ 26

6 Discussion and open problems **27**

7 Acknowledgments **27**

A Proof of Proposition 4.3 **30**