arXiv:2406.07681v2 [quant-ph] 18 Jun 2024

Optimized QUBO formulation methods for quantum computing

Dario De Santis[1,*] and Salvatore Tirone[1,2,3], Stefano Marmi[1], Vittorio Giovannetti[4]
Scuola Normale Superiore, Piazza dei Cavalieri 7, I-56126 Pisa, Italy
[2]*QuSoft, Science Park 123, 1098 XG Amsterdam, the Netherlands*
[3]*Korteweg–de Vries Institute for Mathematics, University of Amsterdam, Science Park 105-107, 1098 XG Amsterdam, the Netherlands and*
[4]*NEST, Scuola Normale Superiore and Istituto Nanoscienze-CNR, I-56126 Pisa, Italy*

Quantum computers have strict requirements for the problems that they can efficiently solve. One of the principal limiting factor for the performances of noisy intermediate-scale quantum (NISQ) devices is the number of qubits required by the running algorithm. Several combinatorial optimization problems can be solved with NISQ devices once that a corresponding quadratic unconstrained binary optimization (QUBO) form is derived. Several techniques have been proposed to achieve such reformulations and, depending on the method chosen, the number of binary variables required, and therefore of qubits, can vary considerably. The aim of this work is to drastically reduce the variables needed for these QUBO reformulations in order to unlock the possibility to efficiently obtain optimal solutions for a class of optimization problems with NISQ devices. This goal is achieved by introducing novel tools that allow an efficient use of slack variables, even for problems with non-linear constraints, without the need to approximate the starting problem. We divide our new techniques in two independent parts, called the iterative quadratic polynomial and the master-satellite methods. Hence, we show how to apply our techniques in case of an NP-hard optimization problem inspired by a real-world financial scenario called Max-Profit Balance Settlement (MPBS). We follow by submitting several instances of this problem to two D-wave quantum annealers, comparing the performances of our novel approach with the standard methods used in these scenarios. Moreover, this study allows to appreciate several performance differences between the D-wave Advantage and next-generation Advantage2 quantum annealers. We show that the adoption of our techniques in this context allows to obtain QUBO formulations with significantly fewer slack variables, i.e., around 90% less, and D-wave annealers provide considerably higher correct solution rates, which moreover do not decrease with the input size as fast as when adopting standard techniques.

I. INTRODUCTION

In recent years, many efforts have been devoted to understand to what extent modern noisy intermediate-scale quantum (NISQ) devices can help to solve optimization problems of any sort (see Refs. [1–3] for recent reviews). Particular attention has been paid to their potential to solve NP-hard and NP-complete problems, which most of the times can be formulated as quadratic unconstrained binary optimizations (QUBO). For instance, all famous NP Karp's problems [4] can be casted in this form [5].

The possibility to solve QUBO problems with quantum devices has been studied on several supports, especially on quantum annealers [1–3, 6–8] but also on logical-gate quantum computers [9–12] and Rydberg atom arrays [13–15]. Although these technologies are not expected to solve NP problems efficiently [16, 17], namely providing exponential speed-ups compared to classical strategies, possible polynomial in-time advantages attract great interest. Indeed, given the importance of the real-world applications involved with the solutions of these hard combinatorial problems [2], any achievable improvement is well-received. Exemplary scenarios come from finance [18–23], logistics [24–26] and drug discovery [27].

Consider the situation where we aim to solve a generic constrained optimization problem with a QUBO solver. The first step is to reformulate it in a quadratic unconstrained form, namely as a QUBO. We call *logical variables* those defining the initial problem. The constraints attached to the original problem can be enforced in a QUBO form by employing additional *slack variables*. The larger is the total number of variables, logical and slack, in a QUBO problem, the harder is in general to solve it.

Whereas the well-established procedures to translate optimization problems into QUBOs [28] can be efficient in several scenarios, their implementation can be extremely inefficient at times. To be more precise, we say that a method to obtain these formulations is inefficient for a problem whenever it requires too many slack variables, namely their number is comparable with that of logical variables. In these cases, the practical usefulness of QUBO solvers can be highly limited. For instance, if we have a maximum size for the problems that our solver can receive, any reduction of slack variables allows to increase the total number of logical variables associated to the initial problem, namely larger problems can be tackled. Moreover, the more slack variables we implement, the higher is the connectivity that we require in our QUBO and therefore in the QUBO solver that we aim to use. This consequence can be a very limiting factor for the performances of modern NISQ devices.

The main motivation of this work is to unlock the possibility to solve certain classes of optimization problems with those quantum technologies specialized to solve QUBO problems. For this purpose, we introduce the iterative quadratic polynomial

* dario.desantis@sns.it