

2021–
2025

Assessing fault-tolerant quantum advantage for k-SAT with structure

Martijn Brehm[1] and Jordi Weggemans[2]

[1]University of Amsterdam, Amsterdam, the Netherlands
[2]QuSoft & CWI, Amsterdam, the Netherlands

December 24, 2024

arXiv:2412.13274v2 [quant-ph] 21 Dec 2024

Abstract

For many problems, quantum algorithms promise speedups over their classical counterparts. However, these results predominantly rely on asymptotic worst-case analysis, which overlooks significant overheads due to error correction and the fact that real-world instances often contain exploitable structure. In this work, we employ the hybrid benchmarking method to evaluate the potential of quantum Backtracking and Grover's algorithm against the 2023 SAT competition main track winner in solving random k-SAT instances with tunable structure, designed to represent industry-like scenarios, using both T-depth and T-count as cost metrics to estimate quantum run times. Our findings reproduce the results of Campbell, Khurana, and Montanaro (Quantum '19) in the unstructured case using hybrid benchmarking. However, we offer a more sobering perspective in practically relevant regimes: almost all quantum speedups vanish, even asymptotically, when minimal structure is introduced or when T-count is considered instead of T-depth. Moreover, when the requirement is for the algorithm to *find* a solution within a single day, we find that only Grover's algorithm has the potential to outperform classical algorithms, but only in a very limited regime and only when using T-depth. We also discuss how more sophisticated heuristics could restore the asymptotic scaling advantage for quantum backtracking, but our findings suggest that the potential for practical quantum speedups in more structured k-SAT solving will remain limited.

1. Introduction

Quantum computing holds the promise of revolutionizing numerous fields by solving computational problems faster than classical computers. Optimization problems—which have a special status as they arise almost everywhere in practice—are also commonly identified as candidates to benefit from quantum computing [1]. But how does one show that such a quantum speedup over classical algorithms exists?

In theoretical computer science, the de facto way to do this is to compare *asymptotic worst-case complexity*, where the complexity can be measured at different levels of abstraction (like the number of gates, queries to a certain function, etc.). However, such analysis has two major shortcomings when it comes to what one wants to know in *practice*:

(i) one might not be interested in the worst-case performance—which considers the worst possible performance amongst all problem instances—as the algorithm only has to perform well on a small subset of all possible instances that are encountered in real-life scenarios;

(ii) quantum and classical computers use different types of hardware with different 'unit costs' (i.e. implementation resources), so X quantum gates cannot be directly compared with Y classical gates. Moreover, these abstract measures of complexity might not be easily translatable to universal measures like time, memory, energy usage, etc., one actually is interested in.

To cover item (i) classical algorithms are often compared empirically by measuring their performance on benchmark sets. This is not yet feasible for most quantum algorithms, as quantum hardware is still in its infancy. So what can we do in the meantime to study the expected performance of quantum algorithms on instances of real-life interests, making assumptions about hardware that does not exist as of yet to take into account item (ii)?

To tackle point (ii), Campbell, Khurana and Montanaro proposed an elegant approach to empirically study the performance of a quantum backtracking algorithm [2] and Grover's algorithm [3] on random instances of constraint satisfaction problems (k-SAT and graph colourability), using a cost model that accounts for error-correction [4]. To go beyond asymptotic worst-case analysis, they write out the constants in the query complexity upper bounds of their algorithms, which include as parameters the number of variables n and (for backtracking) the size of the classical backtracking tree $\mathcal{T}$. To estimate the scaling of $\mathcal{T}$ for a class of random problem instances, they sample random instances and compute a fit of the median value of $\mathcal{T}$, giving them upper bounds in terms of just n for both algorithms. They then argue that (if one does not account for the classical processing cost required to decode the surface code) there is a regime such that the estimated number