

2021–
2025



Quantum position verification in one shot: parallel repetition of the f-BB84 and f-routing protocols

Llorenç Escolà-Farràs[1,2] and Florian Speelman[1,2]

[1] *QuSoft, CWI Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[2] *Multiscale Networked Systems (MNS), Informatics Institute, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands*

March 13, 2025

arXiv:2503.09544v1 [quant-ph] 12 Mar 2025

Abstract

Quantum position verification (QPV) aims to verify an untrusted prover's location by timing communication with them. To reduce uncertainty, it is desirable for this verification to occur in a single round. However, previous protocols achieving one-round secure QPV had critical drawbacks: attackers pre-sharing an EPR pair per qubit could perfectly break them, and their security depended on quantum information traveling at the speed of light in vacuum, a major experimental challenge in quantum networks. In this work, we prove that a single round of interaction suffices for secure position verification while overcoming these limitations. We show that security for a one-round protocol can rely only on the size of the classical information rather than quantum resources, making implementation more feasible, even with a qubit error tolerance of up to 3.6%, which is experimentally achievable with current technology — and showing that the timing constraints have to apply only to classical communication. In short, we establish parallel repetition of the f-BB84 and f-routing QPV protocols. As a consequence of our techniques, we also demonstrate an order-of-magnitude improvement in the error tolerance for the sequential repetition version of these protocols, compared to the previous bounds of *Nature Physics 18, 623–626 (2022)*.

Contents

1 Introduction **2**
1.1 Results . . . 3

2 Preliminaries **4**

3 Parallel repetition of $\mathrm{QPV}^{f}_{\mathrm{BB84}}$ **5**
3.1 Improved error-tolerance for $\mathrm{QPV}^{f}_{\mathrm{BB84}}$ . . . 17

4 Parallel repetition of $\mathrm{QPV}^{f:n\to m}_{\mathrm{rout}}$ **18**
4.1 Improved error-tolerance for $\mathrm{QPV}^{f}_{\mathrm{rout}}$ . . . 22

5 Discussion **23**

References **23**

A Proof of Lemma 4.3 **26**