


$\mathsf{QMA} = \mathsf{QMA}_1$ with an infinite counter

Stacey Jeffery[1,2] and Freek Witteveen[1,3]

[1]QuSoft & CWI, Amsterdam
[2]University of Amsterdam
[3]University of Copenhagen

arXiv:2506.15551v1 [quant-ph] 18 Jun 2025

Abstract

A long-standing open problem in quantum complexity theory is whether QMA, the quantum analogue of NP, is equal to QMA_1, its one-sided error variant. We show that $\mathsf{QMA} = \mathsf{QMA}^\infty = \mathsf{QMA}_1^\infty$, where QMA_1^∞ is like QMA_1, but the verifier has an infinite register, as part of their witness system, in which they can efficiently perform a shift (increment) operation. We call this register an "infinite counter", and compare it to a program counter in a Las Vegas algorithm. The result $\mathsf{QMA} = \mathsf{QMA}^\infty$ means such an infinite register does not increase the power of QMA, but does imply perfect completeness.

By truncating our construction to finite dimensions, we get a QMA-amplifier that only amplifies completeness, not soundness, but does so in significantly less time than previous QMA amplifiers. Our new construction achieves completeness $1 - 2^{-q}$ using $O(1)$ calls to each of the original verifier and its inverse, and $O(\log q)$ other gates, proving that QMA has completeness *doubly* exponentially close to 1, i.e. $\mathsf{QMA} = \mathsf{QMA}(1 - 2^{-2^r}, 2^{-r})$ for any polynomial r.

1 Introduction

The complexity class QMA is generally considered to be the quantum analogue of NP, although there are several complexity classes that could claim this title, including the one-sided variant of QMA, QMA_1 (see [Gha24]). QMA is the class of problems $(L_{\text{yes}}, L_{\text{no}}) \subseteq \{0,1\}^* \times \{0,1\}^*$ such that there exists a polynomial-time quantum verifier $V(x)$ such that (see Definition 2.1 for a formal definition):

Completeness: For all $x \in L_{\text{yes}}$, there exists a witness $|\psi\rangle$ such that $V(x)$ accepts $|\psi\rangle$ with probability at least $c = 2/3$.

Soundness: For all $x \in L_{\text{no}}$, for all witnesses $|\psi\rangle$, $V(x)$ accepts with probability at most $s = 1/3$.

Above, we can take any $s \geq 2^{-\mathsf{poly}(n)}$ and $c \leq 1 - 2^{-\mathsf{poly}(n)}$ such that $c - s \geq \frac{1}{\mathsf{poly}(n)}$, where n is the length of the instance x, without changing the complexity class. If we take $c = 1$ (i.e. *perfect completeness*), the class is QMA_1, and it is not known whether this is the same class as QMA.

QMA is actually the quantum analogue of the class MA, which is the same as QMA, except that we restrict to classical circuits $V(x)$ and classical witnesses. The idea behind the name MA, standing for "Merlin-Arthur", is that we can think of the verifier as representing a single-round protocol between a computationally unbounded *prover*, Merlin, and a polynomial-time *verifier* Arthur. Merlin tries to convince Arthur that $x \in L_{\text{yes}}$ by sending him a witness, and Arthur checks this witness using $V(x)$.

The class QMA is the more natural quantum analogue of NP than QMA_1, since it makes sense to let quantum algorithms have two-sided error. Quantum algorithms tend to work imperfectly, and even a perfect quantum algorithm would likely exhibit some error once it is subject to noise in a real-world quantum computer. Moreover, an exact quantum algorithm in one universal quantum gate set will possibly become inexact when converted to another. So it is not practically interesting to restrict to quantum algorithms with no error, or even one-sided error. However, classically we have $\mathsf{MA} = \mathsf{MA}_1$, raising the question of whether the same holds true for quantum, and if not, if