


Will it glue? On short-depth designs beyond the unitary group

Lorenzo Grevink[1], Jonas Haferkamp[2], Markus Heinrich[3], Jonas Helsen[1], Marcel Hinsche[4], Thomas Schuster[5], and Zoltán Zimborás[6]

[1]QuSoft and CWI, Amsterdam, The Netherlands
[2]Saarland University, Saarbrücken, Germany
[3]Institute for Theoretical Physics, University of Cologne, Cologne, Germany
[4]Dahlem Center for Complex Quantum Systems, Freie Universität Berlin, Berlin, Germany
[5]Walter Burke Institute for Theoretical Physics and Institute for Quantum Information and Matter, California Institute of Technology, Pasadena, USA
[6]QTF Centre of Excellence, Department of Physics, University of Helsinki, P.O. Box 43, FI-00014 Helsinki, Finland

arXiv:2506.23925v3 [quant-ph] 16 Sep 2025

We study the formation of short-depth designs beyond the unitary group. We provide a range of results on several groups of broad interest in quantum information science: the Clifford group, the orthogonal group, the unitary symplectic groups, and the matchgate group. For all of these groups, we prove that analogues of unitary designs cannot be generated by any circuit ensemble with light-cones that are smaller than the system size. This implies linear lower bounds on the circuit depth in one-dimensional systems. For the Clifford, orthogonal, and unitary symplectic group, we moreover show that commonly considered circuit ensembles cannot generate designs in sub-linear depth on any circuit architecture. We show this by exploiting observables in the higher-order commutants of each group, which allow one to distinguish any short-depth circuit from truly random. While these no-go results rule out short-depth designs over these subgroups, we prove that slightly weaker forms of randomness—including additive-error state designs and anti-concentration in sampling distributions—nevertheless emerge at logarithmic depths in many cases. Our results reveal that the onset of randomness in shallow quantum circuits is a widespread yet subtle phenomenon, dependent on the interplay between the group itself and the context of its application.

1 Introduction

Random quantum operations are a central tool in quantum information theory and beyond. Applications include a wide range of research fields such as quantum system characterization[1–3], quantum learning[4], quantum supremacy experiments[5], quantum machine learning[6,7], quantum cryptography[8,9], quantum many-body physics[10,11], and quantum gravity[12–14].

A natural, and the most commonly used, candidate for a random class of quantum operations are the Haar-random unitaries given by the unique uniform distribution on the unitary group. While easy to work with in theory, the Haar measure is often far from practical: Standard counting arguments show that exponential circuit depth is required to implement a Haar random unitary[15]. A second, independent objection to Haar-random unitaries is that they require access to a universal gate set, rendering them potentially expensive to implement on early fault-tolerant devices. Significant effort has thus been spent to find low-depth constructions of random unitaries that appear Haar-random to a restricted observer[16–24]. Roughly, these constructions fall into two categories: Approximate unitary k-designs[25] that appear Haar-random to an observer with access to at most k copies of

Lorenzo Grevink: lorenzo.grevink@cwi.nl