

arXiv:2508.17306v4 [quant-ph] 22 Oct 2025

Efficient Non-Adaptive Quantum Algorithms for Tolerant Junta Testing

Zongbo Bao[1,*], Yuxuan Liu[2,3,†], Penghui Yao[4,5,‡], Zekun Ye[6,§], and Jialin Zhang[2,3,¶]

[1]CWI and Qusoft
[2]State Key Lab of Processors, Institute of Computing Technology, Chinese Academy of Sciences, Beijing 100190, China
[3]School of Computer Science and Technology, University of Chinese Academy of Sciences, Beijing 100049, China
[4]State Key Laboratory for Novel Software Technology, New Cornerstone Science Laboratory, Nanjing University, China
[5]Hefei National Laboratory, Hefei 230088, China
[6]College of Computer and Data Science, Fuzhou University, Fuzhou 350116, China

October 23, 2025

Abstract

We consider the problem of deciding whether an n-qubit unitary (or n-bit Boolean function) is ε_1-close to some k-junta or ε_2-far from every k-junta, where k-junta unitaries act non-trivially on at most k qubits and as the identity on the rest, and k-junta Boolean functions depend on at most k variables. For constant numbers $\varepsilon_1, \varepsilon_2$ such that $0 < \varepsilon_1 < \varepsilon_2 < 1$, we show the following.

1. A non-adaptive $O(k \log k)$-query tolerant $(\varepsilon_1, \varepsilon_2)$-tester for k-junta unitaries when $2\sqrt{2}\varepsilon_1 < \varepsilon_2$.
2. A non-adaptive tolerant $(\varepsilon_1, \varepsilon_2)$-tester for k-junta Boolean functions with $O(k \log k)$ quantum queries when $4\varepsilon_1 < \varepsilon_2$.
3. A $2^{\widetilde{O}(k)}$-query tolerant $(\varepsilon_1, \varepsilon_2)$-tester for k-junta unitaries for any $\varepsilon_1, \varepsilon_2$.

The first algorithm provides an exponential improvement over the best-known quantum algorithms [CLL24, ADG25]. The second algorithm shows an exponential quantum advantage over any non-adaptive classical algorithm [CDL+24]. The third tester gives the first tolerant junta unitary testing result for an arbitrary gap.

Besides, we adapt the first two quantum algorithms to be implemented using only single-qubit operations, thereby enhancing experimental feasibility, with a slightly more stringent requirement for the parameter gap.

1 Introduction

Property testing [GGR98] constitutes a fundamental research field in theoretical computer science, aiming to determine whether an object satisfies a certain global property or is far from it using

*zongbo.bao@cwi.nl
†liuyuxuan23s@ict.ac.cn
‡phyao1985@gmail.com
§yezekun@fzu.edu.cn
¶zhangjialin@ict.ac.cn