

Computational complexity of injective projected entangled pair states

Dylan Harley[1], Freek Witteveen[2], and Daniel Malz[1]

[1]Department of Mathematical Sciences, University of Copenhagen, Denmark
[2]Centrum Wiskunde en Informatica and QuSoft, Amsterdam, the Netherlands

November 13, 2025

arXiv:2509.19963v2 [quant-ph] 12 Nov 2025

Abstract

Projected entangled pair states (PEPS) constitute a variational family of quantum states with area-law entanglement. PEPS are particularly relevant and successful for studying ground states of spatially local Hamiltonians. However, computing local expectation values in these states is known to be postBQP-hard. Injective PEPS, where all constituent tensors fulfil an injectivity constraint, are generally believed to be better behaved, because they are unique ground states of spatially local Hamiltonians. In this work, we therefore examine how the computational hardness of contraction depends on the injectivity. We establish that below a constant positive injectivity threshold, evaluating local observables remains postBQP-complete, while above a different constant nontrivial threshold there exists an efficient classical algorithm for the task, resolving an open question from (Anshu et al., STOC '24). We do this by proving that noisy postselected quantum computation can be made fault-tolerant.

1 Introduction

Tensor network states provide a way of parametrising multipartite quantum states with constrained entanglement. This is especially relevant for ground states of lattice Hamiltonians, which in many cases are believed to exhibit area-law entanglement. Projected entangled pair states (PEPS) are a general class of such tensor network states. They are defined through a choice of graph (connecting physical sites through virtual bond spaces), and a choice of tensor at each vertex that maps the incoming bond spaces to a local physical space. PEPS are commonly used to study ground states of lattice Hamiltonians, and correspondingly one often chooses the graph to be a subset of a finite-dimensional lattice, in which case the PEPS have entanglement entropy satisfying an area law. In this work, we are principally concerned with two-dimensional PEPS.

On a one-dimensional lattice, the PEPS construction gives rise to a class known as matrix product states (MPS). Generally, computations involving MPS are much more tractable than their extensions to general PEPS; MPS possess a canonical form for ease of classification, and there are rigorous guarantees for the approximation of gapped ground states in one dimension by MPS. In contrast, the structure theory of PEPS and its canonical forms in two and more dimensions have weaker properties [1, 2], and the precise relation between gapped ground states, area law states and PEPS is not fully understood [3]. Contraction and computation of local observables is efficient for MPS, whereas for PEPS these tasks are known to be postBQP-complete [4] (roughly equivalent to simulating a quantum computer with access to postselection),