

Computational Monogamy of Entanglement and Non-Interactive Quantum Key Distribution

Alex B. Grilo[1], Giulio Malavolta[2], Michael Walter[3,4,5], and Tianwei Zhang[3,6]

[1] Sorbonne Université, CNRS, LIP6
[2] Bocconi University
[3] Faculty of Computer Science, Ruhr University Bochum
[4] Korteweg-de Vries Institute for Mathematics and QuSoft, University of Amsterdam
[5] Faculty of Physics, Ludwig Maximilian University of Munich
[6] Max Planck Institute for Security and Privacy

arXiv:2510.00791v1 [quant-ph] 1 Oct 2025

Abstract. Quantum key distribution (QKD) enables Alice and Bob to exchange a secret key over a public, untrusted quantum channel. Compared to classical key exchange, QKD achieves *everlasting security*: after the protocol execution the key is secure against adversaries that can do unbounded computations. On the flip side, while classical key exchange can be achieved non-interactively (with two simultaneous messages between Alice and Bob), no non-interactive protocol is known that provides everlasting security, even using quantum information.

In this work, we make progress on this problem. Our main technical contribution is a *computational* variant of the celebrated *monogamy of entanglement* game, where the secret is only computationally hidden from the players, rather than information-theoretically. In these settings, we prove a negligible bound on the maximal winning probability over all strategies. As a direct application, we obtain a non-interactive (simultaneous message) QKD protocol from any post-quantum classical non-interactive key exchange, which satisfies everlastingly secure *assuming Alice and Bob agree on the same key*. The protocol only uses EPR pairs and standard and Hadamard basis measurements, making it suitable for near-term quantum hardware. We also propose how to convert this protocol into a two-round protocol that satisfies the standard notion of everlasting security.

Finally, we prove a *no-go theorem* which establishes that (in contrast to the case of ordinary multi-round QKD) entanglement is necessary for non-interactive QKD, i.e., the messages sent by Alice and Bob cannot both be unentangled with their respective quantum memories if the protocol is to be everlastingly secure.

1 Introduction

Quantum key distribution (QKD) [1] enables two parties, commonly referred to as Alice and Bob, to securely exchange a secret key over a public, untrusted quantum channel. In contrast to classical key exchange protocols, QKD offers two main advantages: (i) It requires only authenticated classical channels, which can