

2023–
2025



2020–
2024



QuantumBoost: A lazy, yet fast, quantum algorithm for learning with weak hypotheses

Amira Abbas* Yanlin Chen† Tuyen Nguyen‡ Ronald de Wolf§

arXiv:2510.05089v1 [quant-ph] 6 Oct 2025

Abstract

The technique of combining multiple votes to enhance the quality of a decision is the core of boosting algorithms in machine learning. In particular, boosting provably increases decision quality by combining multiple "weak learners"—hypotheses that are only slightly better than random guessing—into a single "strong learner" that classifies data well. There exist various versions of boosting algorithms, which we improve upon through the introduction of QuantumBoost. Inspired by classical work by Barak, Hardt and Kale, our QuantumBoost algorithm achieves the best known runtime over other boosting methods through two innovations. First, it uses a quantum algorithm to compute approximate Bregman projections faster. Second, it combines this with a lazy projection strategy, a technique from convex optimization where projections are performed infrequently rather than every iteration. To our knowledge, QuantumBoost is the first algorithm, classical or quantum, to successfully adopt a lazy projection strategy in the context of boosting.

1 Introduction

With its simplicity and provable efficiency, boosting is one of the few algorithmic frameworks in machine learning that is both well-understood theoretically and widely used in practice. The idea was first posed by Kearns and Valiant [KV94] in the context of probably approximately correct (PAC) learning [Val84]. They conjectured the ability to "boost" a weak learning algorithm, which performs slightly better than random guessing, into a strong learning algorithm with an arbitrarily small generalization error. Schapire [Sch90] was the first to introduce such a provably polynomial-time boosting algorithm, followed by Freund [Fre95] who further improved the efficiency – although practical bottlenecks still persisted. These bottlenecks were alleviated through the introduction of AdaBoost, a remarkable algorithm created by Freund and Schapire [FS97] which, till this day, remains competitive for various machine learning tasks [AHK12, VJ01, DWV99, FS96].

For illustration, consider the canonical task of binary classification. We start from a training set $S = \{(x_i, y_i)\}_{i=1}^m$ where each $x_i \in \mathcal{X}$ is distributed according to some (possibly unknown) distribution D, and labeled with a $y_i \in \mathcal{Y}$. These labels could, for instance, be chosen according to some unknown target function $f : \mathcal{X} \to \mathcal{Y}$ that we want to learn. For

*Google Quantum AI, Venice, California, 90291, USA. amiraabbas@google.com

†University of Maryland, College Park, MD 20742, USA. yanlin@umd.edu

‡University of Technology Sydney, Ultimo, NSW, Australia. Tuyen.Q.Nguyen@student.uts.edu.au

§QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium, 024.003.037. rdewolf@cwi.nl