




Clifford testing: algorithms and lower bounds

Marcel Hinsche* Zongbo (Bob) Bao† Philippe van Dordrecht ‡ Jens Eisert §
Jop Briët ¶ Jonas Helsen‖

October 9, 2025

arXiv:2510.07164v1 [quant-ph] 8 Oct 2025

Abstract

We consider the problem of Clifford testing, which asks whether a black-box n-qubit unitary is a Clifford unitary or at least ε-far from every Clifford unitary. We give the first 4-query Clifford tester, which decides this problem with probability $\mathrm{poly}(\varepsilon)$. This contrasts with the minimum of 6 copies required for the closely-related task of stabilizer testing. We show that our tester is tolerant, by adapting techniques from tolerant stabilizer testing to our setting. In doing so, we settle in the positive a conjecture of Bu, Gu and Jaffe, by proving a polynomial inverse theorem for a non-commutative Gowers 3-uniformity norm. We also consider the restricted setting of single-copy access, where we give an $O(n)$-query Clifford tester that requires no auxiliary memory qubits or adaptivity. We complement this with a lower bound, proving that any such, potentially adaptive, single-copy algorithm needs at least $\Omega(n^{1/4})$ queries. To obtain our results, we leverage the structure of the commutant of the Clifford group, obtaining several technical statements that may be of independent interest.

1 Introduction

Stabilizer testing—deciding whether an unknown state is close to a stabilizer state or far from every stabilizer state—has recently seen several remarkable advances [GNW21, GIKL24, IL24]. While the task originates in quantum property testing [MdW16], subsequent work has revealed deep connections to other areas of quantum information theory, mathematics and computer science. In particular, stabilizer testing is directly linked to the representation theory of the Clifford group [GNW21], to the resource theory of magic [BGJ25c, BL25] and quadratic Fourier analysis [AD25, BvDH25, MT25]. These insights have led to steadily improving stabilizer testers, but also to surprising advances in classical algebraic property testing and algorithmic additive combinatorics [BCS25, ACSDG25], as well as algorithms that operate in the restricted setting of single-copy access [HH25].

In this work, we build on all of these advances and tackle the natural dynamic analog of stabilizer testing, namely *Clifford testing*: given query access to an unknown n-qubit unitary U, determine whether it belongs to the Clifford group or is far from it. Clifford testing has structural similarities to stabilizer testing, but as a form of unitary property testing it has some extra properties that make

*Freie Universität Berlin, m.hinsche@fu-berlin.de
†Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, zongbo.bao@cwi.nl
‡Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, Philippe.Dordrecht@cwi.nl
§Freie Universität Berlin, jense@zedat.fu-berlin.de
¶Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, j.briet@cwi.nl
‖Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, jonas@cwi.nl