



Integrity from Algebraic Manipulation Detection in Trusted-Repeater QKD Networks

Ailsa Robertson[a,1,2], Christian Schaffner[b,1,2] and Sebastian R. Verschoor[c,1,2]

[1] University of Amsterdam, The Netherlands
[2] QuSoft, The Netherlands

arXiv:2602.00069v1 [quant-ph] 20 Jan 2026

Abstract. Quantum Key Distribution (QKD) allows secure communication without relying on computational assumptions, but can currently only be deployed over relatively short distances due to hardware constraints. To extend QKD over long distances, networks of trusted repeater nodes can be used, wherein QKD is executed between neighbouring nodes and messages between non-neighbouring nodes are forwarded using a relay protocol. Although these networks are being deployed worldwide, no protocol exists which provides provable guarantees of integrity against manipulation from both external adversaries and corrupted intermediates. In this work, we present the first protocol that provably provides both confidentiality and integrity. Our protocol combines an existing cryptographic technique, Algebraic Manipulation Detection (AMD) codes, with multi-path relaying over trusted repeater networks. This protocol achieves Information-Theoretic Security (ITS) against the detection of manipulation, which we prove formally through a sequence of games.

Keywords: QKD · quantum key distribution · secret sharing · authentication codes · trusted repeater networks · information theoretic security · provable security

1 Introduction

Parties that can exchange quantum information can use Quantum Key Distribution (QKD) to expand a small shared secret into an arbitrarily long secret [BB84]. The effectiveness of such quantum channels, both in terms of distance and rate of transmission, is currently restricted by hardware limitations. While *quantum repeaters* are able to lift this restriction and establish long-distance end-to-end quantum channels, their realisation is currently restricted to laboratory demonstrations and cannot yet be deployed at scale in a quantum network.

An alternative method for establishing keys over a long distance is to use trusted repeater networks [SPD+10]. In such networks, QKD is executed between neighbouring nodes of the network, and messages between non-neighbouring nodes are then established via a *relay* protocol. In the simplest relay protocol, intermediate neighbours decrypt and re-encrypt: if Alice wants to send a message to Bob, she can encrypt and send it to Ingrid (an intermediate node) using a QKD-generated key. Ingrid can decrypt to recover the message and then re-encrypt and send it to Bob. If more intermediate nodes are required

E-mail: s.r.verschoor@uva.nl (Sebastian R. Verschoor)

[a]Funded by the Dutch National Science Agenda (Nationale Wetenschapsagenda, NWA) by The Dutch Research Council (NWO) under project number 1436.20.002, Quantum Impact on Societal Security.
[b]Partially supported by gravitation project Challenges in Cyber Security (CiCS) with file number 024.006.037 which is financed by the NWO.
[c]Supported by the Dutch National Growth Fund (NGF), as part of the Quantum Delta NL programme.

This work is licensed under a "CC BY 4.0" license.
Date of this document: 2026-02-03.