



Logical information localisation in stabiliser codes via single-qubit measurements

Jelena Mackeprang* [1], Hemant Sharma* [1,2], and Jonas Helsen[1]

[1]QuSoft and CWI, Science Park 123, 1098XG Amsterdam, The Netherlands
[2]QuTech, TU Delft, Delft, The Netherlands

March 2026

arXiv:2609.39980v1 [quant-ph] 30 Sep 2026

Stabiliser path finding (SPF) has previously been introduced as a method to localise logical information in a stabiliser code undergoing loss onto a single pre-specified target qubit, using only one round of single-qubit measurements. When working with limited resources and flying qubits, this fast read-out of logical information is a helpful tool for fault-tolerant communication. In this work, we provide a broad analytical and computational study of localisation via SPF. We introduce g-SPF, where the task is to localise the logical information onto a set of at most g unspecified target qubits. Through analytical arguments based on percolation theory and the disjointness of stabiliser codes, we prove that for i.i.d. qubit loss with probability $p < 1/2$ and sufficiently large planar surface codes, localisation via g-SPF for constant g succeeds with a probability converging to one, which establishes a localisation threshold. Furthermore, we propose and implement two algorithms to solve SPF. The first is exact and formulates SPF as an integer linear program, whereas the second is heuristic and formulates SPF as a decoding problem. We validate both algorithms by numerically reproducing the localisation threshold for the surface code and demonstrate that the heuristic algorithm is considerably faster. Our work significantly reduces the time required to solve SPF compared to current state-of-the-art algorithms, allowing us to study localisation in substantially larger stabiliser codes than previously considered in the literature. Together, these theoretical and computational results open the door to various applications, such as fault-tolerant teleportation and efficient logical fusion.

1 Introduction

Measurement-based quantum computation (MBQC) and communication promise various different future applications, such as secure communication, distributed computing and cryptographic protocols [1, 2, 3, 4, 5]. Photonic hardware is a promising route towards scalable, fast and energy-efficient quantum computation [6, 7]. Photons are naturally suited for MBQC where any computation is performed using only (adaptive) single-qubit measurements and local Clifford operations on a large entangled resource state [8, 9, 10, 11]. They are also the most natural resource used in fusion based quantum computation [12] and of course in quantum communication [13, 14]. However, quantum computation or communication with photons faces the problem of photon loss. Fault-tolerant schemes and suitable quantum error correcting codes for MBQC , quantum communication or fusion based quantum computation are therefore highly sought after [15, 16, 17, 18, 19, 20].

Bell et al. [21] searched for graph codes - stabiliser codes defined with respect to graphs [22, 23]-

*These authors contributed equally to this work.