


Fully tolerant product state testing and closest product state learning

Zongbo Bao * Jonas Helsen † Tuyen Nguyen ‡

October 1st 2026

arXiv:2610.01979v1 [quant-ph] 1 Oct 2026

Abstract

We address the problem of testing whether an unknown n-qudit state ρ is a-close to a product state or b-far away from any product state, as measured in terms of state overlap. We provide a time-efficient algorithm to solve this problem that requires an n-independent number of copies of the unknown state. Our random coloring argument shows that for any unknown state there always exists a partition of $[n]$ into q parts such that the square of the overlap with the closest product state with respect to this partition is only an additive factor $O(1/q)$ larger. This reduces the problem to tolerant testing of q parties, with potentially growing local dimensions. Combining this insight with blockwise spectral projection arguments we can show that the natural k-copy generalization of Harrow & Montanaro's [HM13] product state test provides an efficient tolerant tester.

We use the same random coloring and blockwise spectral projection techniques to obtain a substantially improved algorithm for closest product state learning. In particular we give an algorithm that takes in $\widetilde{O}\big((nd)^2\big)\, 2^{\widetilde{O}(1/\varepsilon^8)}$ copies of the unknown state and produces an ε-approximately optimal product state. The key technical components of this learner are a qudit variant of the Bakshi et al. [BBK+24] high-fidelity product state learning algorithm and a sampling technique based on Werner's optimal cloning channel.

1 Introduction

A generic quantum state on n qudits, $\rho \in \mathsf{D}\left((\mathbb{C}^d)^{\otimes n}\right)$, has a description whose size grows, in general, exponentially with n. An interesting problem is therefore to understand when additional structure permits one to infer useful information about an unknown state without per se reconstructing it completely. Perhaps the most basic such structure is *product structure*. A pure product state has the form

$$|\pi\rangle = |\pi_1\rangle \otimes \cdots \otimes |\pi_n\rangle, \tag{1}$$

for each $|\pi_i\rangle \in \mathbb{C}^d$. Product states are a fundamental class of states, which arise as the zero-entanglement limit of many structured state families, as mean-field approximations in many-body physics [BH13], and as unentangled witnesses in quantum complexity theory [HM13]. They therefore provide a natural setting in which to ask how global structure can be inferred from copies of an unknown quantum state.

There are two basic levels at which one may ask this question. At the decision level, one would like to *test* whether an unknown state has the desired structure, and more generally to

*Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, zongbo.bao@cwi.nl
†Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, jonas@cwi.nl
‡University of Technology Sydney, Sydney, Tuyen.Q.Nguyen@student.uts.edu.au