

A Survey of Quantum Learning Theory

Srinivasan Arunachalam* Ronald de Wolf†

arXiv:1701.06806v3 [quant-ph] 28 Jul 2017

Abstract

This paper surveys quantum learning theory: the theoretical aspects of machine learning using quantum computers. We describe the main results known for three models of learning: exact learning from membership queries, and Probably Approximately Correct (PAC) and agnostic learning from classical or quantum examples.

1 Introduction

Machine learning entered theoretical computer science in the 1980s with the work of Leslie Valiant [Val84], who introduced the model of "Probably Approximately Correct" (PAC) learning, building on earlier work of Vapnik and others in statistics, but adding computational complexity aspects. This provided a mathematically rigorous definition of what it means to (efficiently) learn a target concept from given examples. In the three decades since, much work has been done in computational learning theory: some efficient learning results, many hardness results, and many more models of learning. We refer to [KV94b, AB09, SB14] for general introductions to this area. In recent years practical machine learning has gained an enormous boost from the success of deep learning in important big-data tasks like image recognition, natural language processing, and many other areas; this is theoretically still not very well understood, but it often works amazingly well.

Quantum computing started in the 1980s as well, with suggestions for analog quantum computers by Manin [Man80, Man99], Feynman [Fey82, Fey85], and Benioff [Ben82], and reached more digital ground with Deutsch's definition of a universal quantum Turing machine [Deu85]. The field gained momentum with Shor's efficient quantum algorithms [Sho97] for factoring integers and computing discrete logarithms (which between them break much of today's public-key cryptography), and has since blossomed into a major area at the crossroads of physics, mathematics, and computer science.

Given the successes of both machine learning and quantum computing, combining these two strands of research is an obvious direction. Indeed, soon after Shor's algorithm, Bshouty and Jackson [BJ99] introduced a version of learning from *quantum* examples, which are quantum superpositions rather than random samples. They showed that Disjunctive Normal Form (DNF) can be learned efficiently from quantum examples under the uniform distribution; efficiently learning DNF from uniform *classical* examples (without membership queries) was and is an important open problem in classical learning theory. Servedio and others [AS05, AS09, SG04] studied upper and lower bounds on the number of quantum membership queries or quantum examples needed

*QuSoft, CWI, Amsterdam, the Netherlands. Supported by ERC Consolidator Grant QPROGRESS 615307.

†QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by ERC Consolidator Grant QPROGRESS 615307.

