

Efficient algorithms for tensor scaling, quantum marginals, and moment polytopes

Peter Bürgisser* Cole Franks† Ankit Garg ‡ Rafael Oliveira§
Michael Walter¶ Avi Wigderson ‖

April 17, 2018

arXiv:1804.04739v2 [cs.DS] 16 Apr 2018

Abstract

We present a polynomial time algorithm to approximately *scale* tensors of any format to *arbitrary* prescribed marginals (whenever possible). This unifies and generalizes a sequence of past works on matrix, operator and tensor scaling. Our algorithm provides an efficient weak membership oracle for the associated *moment polytopes*, an important family of implicitly-defined convex polytopes with exponentially many facets and a wide range of applications. These include the entanglement polytopes from quantum information theory (in particular, we obtain an efficient solution to the notorious one-body quantum marginal problem) and the Kronecker polytopes from representation theory (which capture the asymptotic support of Kronecker coefficients). Our algorithm can be applied to succinct descriptions of the input tensor whenever the marginals can be efficiently computed, as in the important case of matrix product states or tensor-train decompositions, widely used in computational physics and numerical mathematics.

Beyond these applications, the algorithm enriches the arsenal of "numerical" methods for classical problems in invariant theory that are significantly faster than "symbolic" methods which explicitly compute invariants or covariants of the relevant action. We stress that (like almost all past algorithms) our convergence rate is polynomial in the approximation parameter; it is an intriguing question to achieve exponential convergence rate, beating symbolic algorithms exponentially, and providing *strong* membership and separation oracles for the problems above.

We strengthen and generalize the alternating minimization approach of previous papers by introducing the theory of highest weight vectors from representation theory into the numerical optimization framework. We show that highest weight vectors are natural potential functions for scaling algorithms and prove new bounds on their evaluations to obtain polynomial-time convergence. Our techniques are general and we believe that they will be instrumental to obtain efficient algorithms for moment polytopes beyond the ones consider here, and more broadly, for other optimization problems possessing natural symmetries.

*Institut für Mathematik, Technische Universität Berlin, email: pbuerg@math.tu-berlin.de.
†Department of Mathematics, Rutgers University, email: wcf17@math.rutgers.edu.
‡Microsoft Research New England, email: garga@microsoft.com.
§Department of Computer Science, University of Toronto, email: rafael@cs.toronto.edu.
¶QuSoft, Korteweg-de Vries Institute for Mathematics, Institute of Physics, and Institute for Logic, Language and Computation, University of Amsterdam, email: m.walter@uva.nl.
‖Institute for Advanced Study, Princeton, email: avi@ias.edu.

