

Quantum Algorithms for Connectivity and Related Problems

MICHAEL JARRET[1], STACEY JEFFERY[2], SHELBY KIMMEL[3], AND ALVARO PIEDRAFITA[2]

[1]*Perimeter Institute*
[2]*Qusoft, CWI*
[3]*Middlebury College*

arXiv:1804.10591v1 [quant-ph] 27 Apr 2018

Abstract

An important family of span programs, *st*-connectivity span programs, have been used to design quantum algorithms in various contexts, including a number of graph problems and formula evaluation problems. The complexity of the resulting algorithms depends on the largest *positive witness size* of any 1-input, and the largest *negative witness size* of any 0-input. Belovs and Reichardt first showed that the positive witness size is exactly characterized by the effective resistance of the input graph, but only rough upper bounds were known previously on the negative witness size. We show that the negative witness size in an *st*-connectivity span program is exactly characterized by the *capacitance* of the input graph. This gives a tight analysis for algorithms based on *st*-connectivity span programs on any set of inputs.

We use this analysis to give a new quantum algorithm for estimating the capacitance of a graph. We also describe a new quantum algorithm for deciding if a graph is connected, which improves the previous best quantum algorithm for this problem if we're promised that either the graph has at least $\kappa > 1$ components, or the graph is connected and has small *average resistance*, which is upper bounded by the diameter. We also give an alternative algorithm for deciding if a graph is connected that can be better than our first algorithm when the maximum degree is small. Finally, using ideas from our second connectivity algorithm, we give an algorithm for estimating the *algebraic connectivity* of a graph, the second largest eigenvalue of the Laplacian.

1 Introduction

Span programs are an algebraic model of computation first developed by Karchmer and Wigderson [KW93] to study classical logspace complexity, and introduced to the study of quantum algorithms by Reichardt and Špalek [RŠ12]. In [Rei11, Rei09], Reichardt used the concept of span programs to prove that the general adversary bound gives a tight lower bound on the quantum query complexity of any given decision problem, thus showing the deep connection between span programs and quantum query algorithms.

Given a span program, a generic transformation compiles it into a quantum algorithm, whose query complexity is analyzed by taking the geometric mean of two quantities: the largest *positive witness size* of any 1-input; and the largest *negative witness size* of any 0-input. Thus, in order to analyze the query complexity of an algorithm obtained in this way, it is necessary to characterize, or at least upper bound, these quantities. Moreover, there is always a span program based algorithm with asymptotically optimal quantum query complexity [Rei11, Rei09].

The relationship between quantum query algorithms and span programs is potentially a powerful tool, but this correspondence alone is not a recipe for finding such an algorithm, and actually producing an optimal (or even good) span program for a given problem is generally difficult. Despite this difficulty, a number of span programs have been found for important problems such as *k*-distinctness [Bel12a], formula evaluation [RŠ12, Rei10], and *st*-connectivity [BR12]. The latter span program is of particular importance, as it has been applied to a number of graph problems [CMB16], to generic formula evaluation problems [JK17], and underlies the learning graph framework [Bel12b]. The *st*-connectivity based algorithms are also of interest because, unlike with generic span program algorithms, it is often possible to analyze not only query complexity, but also the time complexity.

