

arXiv:1811.10090v1 [quant-ph] 25 Nov 2018

Exponential Separation between Quantum Communication and Logarithm of Approximate Rank

Makrand Sinha* Ronald de Wolf†

Abstract

Chattopadhyay, Mande and Sherif [CMS18] recently exhibited a total Boolean function, the *sink* function, that has polynomial approximate rank and polynomial randomized communication complexity. This gives an exponential separation between randomized communication complexity and logarithm of the approximate rank, refuting the log-approximate-rank conjecture. We show that even the *quantum* communication complexity of the sink function is polynomial, thus also refuting the quantum log-approximate-rank conjecture.

Our lower bound is based on the fooling distribution method introduced by Rao and Sinha [RS15] for the classical case and extended by Anshu, Touchette, Yao and Yu [ATYY17] for the quantum case. We also give a new proof of the classical lower bound using the fooling distribution method.

1 Introduction

Communication complexity [KN97, RY18] is a basic model of distributed computing where one only cares about the resource of *communication* between the various distributed parties doing the computation. This is a beautiful and fundamental computational model in its own right, and has many applications to other areas, in particular for lower bounds. For concreteness consider the two-player communication complexity of some Boolean function $f : \{0,1\}^n \times \{0,1\}^n \to \{0,1\}$. Here Alice receives input $x \in \{0,1\}^n$ and Bob receives input $y \in \{0,1\}^n$, and they want to compute $f(x,y)$ with minimal communication between them.

Much research has gone into relating the (deterministic, randomized, nondeterministic, quantum, ...) communication complexity of f to its combinatorial or algebraic properties. In particular, we may consider the relation between the communication complexity and the *rank* (over the reals) of the $2^n \times 2^n$ Boolean matrix M_f whose entries are the values $f(x,y)$. Mehlhorn and Schmidt [MS82] showed that the log of this rank lower bounds the deterministic communication complexity of f, and Lovász and Saks [LS93] conjectured that this lower bound is polynomially tight; in other words, that deterministic communication complexity is upper bounded by a polynomial in the logarithm of the rank of M_f. This *log-rank conjecture* is one of the main open problems in communication complexity and remains wide open. On the one hand, the best upper bound on deterministic communication complexity in terms of rank is roughly the *square root* of the rank [Lov16, Lov14] (see also [Rot14]). On the other hand, the biggest known gap between deterministic communication complexity and log-rank is only quadratic [GPW15].

*CWI, the Netherlands. Supported by the Netherlands Organization for Scientific Research, Grant Number 617.001.351. makrand.sinha@cwi.nl

†QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by ERC Consolidator Grant 615307-QPROGRESS and by QuantERA project QuantAlgo 680-91-034. rdewolf@cwi.nl

