

Robust self-testing of two-qubit states

Tim Coopmans,[1] Jędrzej Kaniewski,[2] and Christian Schaffner[3]

[1] *QuTech, Delft University of Technology, Lorentzweg 1, 2628 CJ Delft, The Netherlands*
[2] *Center for Theoretical Physics, Polish Academy of Sciences, Al. Lotników 32/46, 02-668 Warsaw, Poland*
[3] *QuSoft, University of Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands*

(Dated: April 2, 2020)

It is well-known that observing nonlocal correlations allows us to draw conclusions about the quantum systems under consideration. In some cases this yields a characterisation which is essentially complete, a phenomenon known as self-testing. Self-testing becomes particularly interesting if we can make the statement robust, so that it can be applied to a real experimental setup. For the simplest self-testing scenarios the most robust bounds come from the method based on operator inequalities. In this work we elaborate on this idea and apply it to the family of tilted CHSH inequalities. These inequalities are maximally violated by partially entangled two-qubit states and our goal is to estimate the quality of the state based only on the observed violation. For these inequalities we have reached a candidate bound and while we have not been able to prove it analytically, we have gathered convincing numerical evidence that it holds. Our final contribution is a proof that in the usual formulation, the CHSH inequality only becomes a self-test when the violation exceeds a certain threshold. This shows that self-testing scenarios fall into two distinct classes depending on whether they exhibit such a threshold or not.

arXiv:1902.00870v4 [quant-ph] 31 Mar 2020

I. INTRODUCTION

Among the many sins of quantum mechanics, correlations between space-like separated systems occupy a rather special place. Stronger-than-classical correlations [1, 2] were initially seen as a problem, but have now become an inherent (and useful) feature of the quantum world. Investigating the difference between correlations achievable in quantum mechanics and in classical (local-realistic) theories goes under the name of Bell nonlocality [3], and one of the great achievements of this field is the ability to rule out any classical description of the system under consideration based *only* on the observed statistics. While clearly of fundamental importance, it turns out that this argument can be pushed one step further.

If we can rule out a classical description, our next guess is that the system is governed by quantum mechanics. Under this assumption it makes sense to ask which features of the quantum system give rise to such strikingly non-classical behaviour. Can we, for instance, deduce something about the quantum state or the measurements performed?

While it is clear that in order to observe nonlocal correlations one must perform incompatible measurements on entangled quantum systems, it is not clear which meaningful quantitative statements can be made. It might, therefore, come as a surprise that certain nonlocal correlations can be realised in an essentially unique manner. While this observation can be found in the early works of Tsirelson [4, 5], Summers and Werner [6] and Popescu and Rohrlich [7], it did not attract much attention until the seminal work of Mayers and Yao [8, 9]. Mayers and Yao realised that this effect can be used to *certify* quantum devices under minimal assumptions and they called this phenomenon *self-testing*.

The goal of self-testing is to make quantitative statements about the *quantum realisation*, e.g. about the entanglement present in a quantum state or about the incompatibility of the measurements performed. Self-testing is closely related to the field of *device-independent cryptography* whose goal is to certify properties of the classical output produced by quantum devices. Device-independent cryptography is a promising solution for randomness generation [10–15], quantum key distribution [16–21] and several other tasks [22–26]. For a brief overview of device-independent cryptography, we recommend Ref. [27] (focus on quantum key distribution) and Ref. [28] (focus on randomness generation). For a comprehensive review on both philosophical and technological aspects of randomness in quantum physics, we refer the reader to Ref. [29].

In this work, we focus solely on the task of self-testing in its most common formulation, i.e. when the goal is to certify the state and the measurements performed on it.[1] While there is a large class of scenarios in which self-testing statements have been proven, most results only apply if the observed statistics are (almost) perfect [34–47]. While such results are *robust* in the sense that they are stable under sufficiently small perturbations, the obtained noise tolerance is not relevant from the experimental point of view. Our goal, on the other hand, is to derive self-testing statements which can be applied to real statistics collected in real experiments.[2] Such results are of interest to both experimentalists [49–51] and theoreticians investigating specific physical setups [52], but deriving them turns out to be significantly more challenging.

The first result of this type is due to Bardyn et al. [34] and there are currently two methods of deriving such results: the "swap method" [53–55] and the "self-testing from operator inequalities (STOPI) method" [56]. While the swap method is extremely versatile and can be (at least in principle) immediately applied to any Bell scenario, it has two weaknesses. First of all, it is a numerical method which scales unfavourably with the dimension of the system we wish to certify: the largest states certified

[1] Note that other quantum objects such as quantum channels [30] entangled measurements [31, 32] or weak measurements [33] ca be self-tested in more complex scenarios.
[2] For an intuitive explanation of the difference between robustnes and experimentally-relevant robustness see Section I of Ref. [48