

2018–202

arXiv:1909.13528v1 [quant-ph] 30 Sep 2019

Quantum gradient estimation of Gevrey functions

Arjan Cornelissen*

October 1, 2019

Abstract

Gradient-based numerical methods are ubiquitous in optimization techniques frequently applied in industry to solve practical problems. Often times, evaluating the objective function is a complicated process, so estimating the gradient of a function with as few function evaluations as possible is a natural problem.

We investigate whether quantum computers can perform ℓ^∞-approximate gradient estimation of multivariate functions $f : \mathbb{R}^d \to \mathbb{R}$ with fewer function evaluations than classically. Following previous work by Jordan [Jor05] and Gilyén et al. [GAW19], we prove that one can calculate an ℓ^∞-approximation of the gradient of f with a query complexity that scales sublinearly with d under weaker smoothness conditions than previously considered.

Furthermore, for a particular subset of smoothness conditions, we prove a new lower bound on the query complexity of the gradient estimation problem, proving essential optimality of Gilyén et al.'s gradient estimation algorithm in a broader range of parameter values, and affirming the validity of their conjecture [GAW19]. Moreover, we improve their lower bound qualitatively by showing that their algorithm is also optimal for functions that satisfy the imposed smoothness conditions globally instead of locally. Finally, we introduce new ideas to prove lower bounds on the query complexity of the ℓ^p-approximate gradient estimation problem where $p \in [1, \infty)$, and prove that lifting Gilyén et al.'s algorithm to this domain in the canonical manner is essentially optimal.

1 Introduction

Function optimization is a fundamental problem in mathematics and computer science. It finds many real-world applications and is typically used as a tool to tweak continuous parameters to maximize profit or minimize cost. As the field of quantum computing is progressing at a fast pace, the question whether quantum effects can be used to speed up the process of function optimization arises naturally.

There exist many classical algorithms that perform function optimization. One of the most well-known is gradient ascent/descent. The algorithm first makes a random guess in the domain of the objective function, and then iteratively updates this guess in the direction in which the function changes fastest. This direction is determined by the *gradient* of the function, and hence in every iteration this gradient is to be calculated. In this paper, we look at whether this gradient calculation step can be sped up using quantum effects.

The functions that one tries to optimize are typically not given in closed form, and hence calculating the gradient can often not be done using analytical methods. Instead, one usually treats the function as a *black box*, and then resorts to numerical methods that *estimate* the gradient based on several function evaluations.



*QuSoft / CWI / UvA, Science Park 123, 1098 XG Amsterdam, Netherlands. arjan@cwi.nl