

2017–2021

arXiv:1910.05729v1 [quant-ph] 13 Oct 2019

Efficient simulation of random states and random unitaries

Gorjan Alagic[1,2], Christian Majenz[3,4], and Alexander Russell[5]

[1] Joint Center for Quantum Information and Computer Science, University of Maryland
[2] National Institute of Standards and Technology, Gaithersburg, Maryland
[3] QuSoft, Amsterdam
[4] Centrum Wiskunde & Informatica, Amsterdam
[5] Department of Computer Science and Engineering, University of Connecticut

Abstract. We consider the problem of efficiently simulating random quantum states and random unitary operators, in a manner which is convincing to unbounded adversaries with black-box oracle access.

This problem has previously only been considered for restricted adversaries. Against adversaries with an a priori bound on the number of queries, it is well-known that t-designs suffice. Against polynomial-time adversaries, one can use pseudorandom states (PRS) and pseudorandom unitaries (PRU), as defined in a recent work of Ji, Liu, and Song; unfortunately, no provably secure construction is known for PRUs.

In our setting, we are concerned with unbounded adversaries. Nonetheless, we are able to give stateful quantum algorithms which simulate the ideal object in both settings of interest. In the case of Haar-random states, our simulator is polynomial-time, has negligible error, and can also simulate verification and reflection through the simulated state. This yields an immediate application to quantum money: a money scheme which is information-theoretically unforgeable and untraceable. In the case of Haar-random unitaries, our simulator takes polynomial space, but simulates both forward and inverse access with zero error.

These results can be seen as the first significant steps in developing a theory of lazy sampling for random quantum objects.

1 Introduction

1.1 Motivation

Efficient simulation of randomness is a task with countless applications, ranging from cryptography to derandomization. In the setting of classical probabilistic computation, such simulation is straightforward in many settings. For example, a random function which will only be queried an a priori bounded number of times t can be perfectly simulated using a t-wise independent function [31]. In the case of unbounded queries, one can use pseudorandom functions (PRFs), provided the queries are made by a polynomial-time algorithm [16]. These are examples of *stateless* simulation methods, in the sense that the internal memory of the simulator is initialized once (e.g., with the PRF key) and then remains fixed regardless of how the simulator is queried. Against arbitrary adversaries, one must typically pass to *stateful* simulation. For example, the straightforward and well-known technique of *lazy sampling* suffices to perfectly simulate a random function against arbitrary adversaries; however, the simulator must maintain a list of responses to all previous queries.

Each of these techniques for simulating random classical primitives has a plethora of applications in theoretical cryptography, both as a proof tool and for cryptographic constructions. These range from constructing secure cryptosystems for encryption and authentication, to proving security reductions in a wide range of settings, to establishing security in idealized models such as the Random Oracle Model [6].

Quantum randomness. As is well-known, quantum sources of randomness exhibit dramatically different properties from their classical counterparts [23,7]. Compare, for example, uniformly random n-bit classical states (i.e., n-bit strings) and uniformly random n-qubit (pure) quantum states. A random string x is obviously trivial to sample perfectly given probabilistic classical (or quantum) computation, and can be

