

2020⊠2022



arXiv:2012.05233v2 [quant-ph] 25 Apr 2023

The Role of Symmetry in Quantum Query-to-Communication Simulation*

Sourav Chakraborty† Arkadev Chattopadhyay‡ Peter Høyer§ Nikhil S. Mande¶
Manaswi Paraashar‖ Ronald de Wolf**

Abstract

Buhrman, Cleve and Wigderson (STOC'98) showed that for every Boolean function $f : \{-1,1\}^n \to \{-1,1\}$ and $G \in \{\mathsf{AND}_2, \mathsf{XOR}_2\}$, the bounded-error quantum communication complexity of the composed function $f \circ G$ equals $O(\mathsf{Q}(f) \log n)$, where $\mathsf{Q}(f)$ denotes the bounded-error quantum query complexity of f. This is achieved by Alice running the optimal quantum query algorithm for f, using a round of $O(\log n)$ qubits of communication to implement each query. This is in contrast with the classical setting, where it is easy to show that $\mathsf{R}^{cc}(f \circ G) \leq 2\mathsf{R}(f)$, where R^{cc} and R denote bounded-error communication and query complexity, respectively. We show that the $O(\log n)$ overhead is required for some functions in the quantum setting, and thus the BCW simulation is tight. We note here that prior to our work, the possibility of $\mathsf{Q}^{cc}(f \circ G) = O(\mathsf{Q}(f))$, for all f and all $G \in \{\mathsf{AND}_2, \mathsf{XOR}_2\}$, had not been ruled out. More specifically, we show the following.

- We show that the $\log n$ overhead is *not* required when f is symmetric (i.e., depends only on the Hamming weight of its input), generalizing a result of Aaronson and Ambainis for the Set-Disjointness function (Theory of Computing'05). This upper bound assumes a shared entangled state, though for most symmetric functions the assumed number of entangled qubits is less than the communication and hence could be part of the communication.
- In order to prove the above, we design an efficient distributed version of noisy amplitude amplification that allows us to prove the result when f is the OR function.
- In view of our first result above, one may ask whether the $\log n$ overhead in the BCW simulation can be avoided even when f is transitive, which is a weaker notion of symmetry. We give a strong negative answer by showing that the $\log n$ overhead is still necessary for some transitive functions even when we allow the quantum communication protocol an error probability that can be arbitrarily close to $1/2$ (this corresponds to the unbounded-error model of communication).

*Preliminary versions of this work appeared in CCC'20 [CCMP20] and STACS'22 [CCH+22].

†Indian Statistical Institute, Kolkata. sourav@isical.ac.in

‡TIFR, Mumbai. Partially supported by the MATRICS grant MTR/2019/001633 of the Science and Engineering Research Board, DST, India. arkadev.c@tifr.res.in

§Department of Computer Science, University of Calgary, Canada. hoyer@ucalgary.ca

¶University of Liverpool, UK. Part of this work was done while the author was a postdoc at Georgetown University, and at CWI and QuSoft, supported by the Dutch Research Council (NWO) through QuantERA project QuantAlgo 680-91-034 and by the Quantum Software Consortium programme (project number 024.003.037). Nikhil.Mande@liverpool.ac.uk.

‖Aarhus University, Denmark. Work done while at Indian Statistical Institute, Kolkata. manaswi.isi@gmail.com

**QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by ERC Consolidator Grant 615307-QPROGRESS (which ended February 2019), and by the Dutch Research Council (NWO/OCW), as part of the Quantum Software Consortium programme (project number 024.003.037), and through QuantERA ERA-NET Cofund project QuantAlgo (680-91-034). rdewolf@cwi.nl

