

A benchmarking procedure for quantum networks

Jonas Helsen[1] and Stephanie Wehner[2,3]

[1]*Qusoft & Korteweg-de Vries Instituut, University of Amsterdam, Science Park 123 1098 XG Amsterdam, The Netherlands*
[2]*QuTech, Delft University of Technology, Lorentzweg 1, 2628 CJ Delft, The Netherlands*
[3]*Kavli Institute of Nanoscience, Delft University of Technology, Lorentzweg 1, 2628 CJ Delft, The Netherlands*

(Dated: March 2, 2021)

We propose network benchmarking: a procedure to efficiently benchmark the quality of a quantum network link connecting quantum processors in a quantum network. This procedure is based on the standard randomized benchmarking protocol and provides an estimate for the fidelity of a quantum network link. We provide statistical analysis of the protocol as well as a simulated implementation inspired by NV-center systems using Netsquid, a special purpose simulator for noisy quantum networks.

arXiv:2103.01165v1 [quant-ph] 1 Mar 2021

I. INTRODUCTION

Quantum technology research can be broadly categorized into two strands: on the one hand the development of large-scale fault-tolerant quantum computers, and on the other hand the development of quantum networks that link quantum computers together and allow for quantum communication based tasks (such as clock synchronization [1], anonymous communication [2], and cryptography [3, 4]), culminating in a Quantum Internet [5] connecting quantum processing nodes. These nodes, for which physical platforms such as NV-centers in diamond [6], ion traps [7], and neutral atoms [8] are currently being developed, posses quantum computing capacity, leading to the possibility of distributed or networked quantum computing [9].

One of the major step changes in the development of quantum computers in the last decade has been the development of practical methods to characterize the quality of quantum operations, allowing experimentalists to quickly diagnose and improve a critical building block of a fault-tolerant quantum computing architecture (see e.g. [10] and references therein). In this work we consider the corresponding problem of the characterization of quantum communication links, a key feature of quantum networks that has no real counterpart in quantum computation. Several methods exist to assess the quality of a quantum network link which we briefly review. For entanglement based networks, i.e. networks where the quantum network link is established through entangled states between nodes, any characterization of the quality of entanglement translates in principle to a quality measure of the network link. Many methods exist to assess the quality of entanglement (see e.g. [11, 12] for work on Bell inequalities and self-testing, and [13] for quantum state tomography), which can be mapped to quality-assessment methods for quantum network links. Similarly, for direct transmission based network links (abstractly modeled by a quantum channel), we may, from the transmission of qubit states in two distinct bases (typically the X and Z bases) make an inference about how well any state, or indeed entanglement, may be transmitted (see e.g.[14–16]). More generally, a procedure is known to estimate the capacity of a quantum channel [17]). Finally, [18] gives a method certify whether a quantum network of nodes connected by quantum links has attained a specific stage of development.

In this work we aim to add to this toolbox by proposing network benchmarking: a procedure to assess the quality of transmission between quantum processing nodes in a quantum network in the so-called *quantum memory network stage* and above [5], by yielding an estimate of the average fidelity of the effective quantum channel modeling a quantum network link. Network benchmarking is adapted from the randomized benchmarking protocol [19, 20], a gold-standard methodology for the characterization of quantum operations in quantum computers. It is lightweight, easy to implement, and inherits many of the robustness properties enjoyed by the original randomized benchmarking protocol. We also give a more general multi-node protocol that can be used to characterize the fidelity of a path of multiple nodes connected by quantum communication links, and can thus be seen as the quantum analogon to the classical 'ping' operation.

A. Results

We introduce network benchmarking, a method that robustly and efficiently yields an estimate of the quality of a quantum network link. We propose two version of this protocol: a 2-node protocol that estimates the quality of a link between two quantum network nodes, and a multi-node protocol that estimates the quality of a path over several nodes in a network. We provide a theoretical analysis of these protocols, arguing that they estimate the average fidelity of the quantum channel modeling a quantum link. For network links implemented by noisy quantum teleportation we prove that this network fidelity can be related to the *average fidelity*, a standard metric of quality of quantum processes.

We supplement this theoretical work with numerical simulations using the quantum network simulator Netsquid [21]. By testing several realistic scenarios we

