

2021–2022

Error mitigation and quantum-assisted simulation in the error corrected regime

M. Lostaglio[1,2] and A. Ciani[1,3]

[1] *QuTech, Delft University of Technology, P.O. Box 5046, 2600 GA Delft, The Netherlands*
[2] *Korteweg-de Vries Institute for Mathematics and QuSoft, University of Amsterdam, The Netherlands*
[3] *JARA Institute for Quantum Information, Forschungszentrum Jülich, D-52425 Jülich, Germany*

A standard approach to quantum computing is based on the idea of promoting a classically simulable and fault-tolerant set of operations to a universal set by the addition of 'magic' quantum states. In this context, we develop a general framework to discuss the value of the available, non-ideal magic resources, relative to those ideally required. We single out a quantity, the Quantum-assisted Robustness of Magic (QRoM), which measures the overhead of simulating the ideal resource with the non-ideal ones through quasiprobability-based methods. This extends error mitigation techniques, originally developed for Noisy Intermediate Scale Quantum (NISQ) devices, to the case where qubits are logically encoded. The QRoM shows how the addition of noisy magic resources allows one to boost classical quasiprobability simulations of a quantum circuit and enables the construction of explicit protocols, interpolating between classical simulation and an ideal quantum computer.

arXiv:2103.07526v3 [quant-ph] 11 Apr 2022

Introduction. Large-scale quantum computing would allow us to solve computational problems that are intractable for classical computers. Due to the fragility of quantum information encoded in physical systems, quantum error correction will be a central component of these machines. However, several restrictions exist to the possibility of achieving a 'universal' set of fault-tolerant quantum gates [1, 2]. In a standard setting, the *stabilizer operations* (which involve computational basis preparation and measurement, Clifford unitaries, partial trace and classical randomness [3, 4]) are fault-tolerant and hence 'free'. Curiously, the Gottesman-Knill theorem tells us that these operations can be simulated efficiently on a classical computer [3, 5]. Stabilizer operations can be promoted to universality by injecting *magic states*, which are thus a 'resource' for quantum computation. Magic states may come at a limited rate, since their fault-tolerant preparation involves complex distillation schemes [6–11]. Also, much of the residual noise in an error-corrected computation can originate from these elements.

In this work we go beyond the dichotomy free/resourceful and think in terms of the resource content of an ideal quantum resource *relative* to an available one. We formulate questions such as "How valuable is an ideal magic state, compared to its noisy version, as a function of the noise level?" or "How valuable are the r available magic states, compared to the $t > r$ ideally needed?". Our notion of relative value stems from the overhead of simulating ideal resources with non-ideal ones through quasiprobability based error mitigation [12–16]. As such, it is endowed with a clear operational significance.

Quasiprobability-based error mitigation is a technique that allows one to remove bias from the outcome probabilities of a measurement by expressing the ideal circuit elements as linear combinations of non-ideal ones. The coefficients of the decomposition define a quasiprobability, since they are real and sum to one. By sampling from the absolute value of this quasiprobability and performing the corresponding non-ideal operations, one can remove the bias at the price of a sampling overhead.

We extend these ideas from Noisy Intermediate-Scale Quantum devices (NISQ) [12–16] to fault-tolerant quantum computing. In this context, we single out a measure, the Quantum-assisted Robustness of Magic (QRoM), which loosely speaking is a distance of the ideal elements relative to the available ones. The QRoM provides a unified setting to analyse several central computational and simulation tasks, investigated separately in the literature:

(1) Classical simulation: classically sample from the outcome probabilities of an ideal quantum circuit with t magic T-states $|T\rangle = (|0\rangle + e^{i\pi/4}|1\rangle)/\sqrt{2}$ as input (t is known as the T-count). Having no quantum resources at hand, the QRoM coincides with the Robustness of Magic (RoM), a known measure of the overhead of quasiprobability-based classical simulation [4, 17–19].

(2) Error mitigation in the quantum error corrected regime: given a quantum circuit involving t ideal T-states, obtain the average of measurement outcomes using a circuit with t noisy T-states. The overhead is measured by the QRoM [20].

(3) Quantum-Assisted Simulation: obtain the average of measurement outcomes of an ideal quantum circuit involving t ideal T-states, given that we can inject only $r < t$ noisy T-states. This task can be seen as an intermediate scenario between classical simulation ($r = 0$) and error mitigation ($r = t$), where some quantum resources are available but fewer than what is needed. The residual overhead is quantified by the QRoM.

By analytically or numerically solving optimization problems for the QRoM, we construct quasiprobability-based error mitigation and quantum-assisted simulation algorithms in the error corrected regime, and analyze how the addition of quantum resources gradually interpolates between a classical simulation and an ideal quantum computation.

Quantum-assisted Robustness of Magic. The QRoM is a generalization of the RoM and formalizes the idea of robustness of an ideal quantum computational resource relative to the (fewer, noisier) available ones. Consider a quantum computer where magic states are injected by

